

**CONTACT INFORMATION**

- Website: [www.supermicro.com](http://www.supermicro.com)
- General Information: [marketing@supermicro.com](mailto:marketing@supermicro.com)
- Technical Support: [support@supermicro.com](mailto:support@supermicro.com)
- Phone: +1 (408) 503-8000, Fax: +1 (408) 503-8008

**FOR YOUR SYSTEM TO WORK PROPERLY, PLEASE DOWNLOAD APPROPRIATE**

**DRIVERS/IMAGES/USER'S MANUAL FROM THE LINKS BELOW:**


- Manuals: <http://www.supermicro.com/support/manuals>
- Drivers & Utilities: <https://www.supermicro.com/wdl/driver>
- Safety: [http://www.supermicro.com/about/policies/safety\\_information.cfm](http://www.supermicro.com/about/policies/safety_information.cfm)

**PACKAGE CONTENTS**

- One (1) Supermicro Motherboard
- Two (2) SATA Cables
- One (1) Quick Reference Guide

**WARNING:** This product can expose you to chemicals including lead, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



**Motherboard Layout and Features**



Note: NVMe slots are available for the -NT model only.

→ = mounting hole

**CPU/Heatsink Installation**



Notes: 1. Please refer to Chapter 2 of the user's manual for detailed instructions of CPU/Heatsink and memory Installation. 2. Graphics shown in this quick reference guide are for illustration only. Your components may or may not look exactly the same as drawings shown in this guide.

**Front Panel Control (JF1)**

Power Button	1	2	Ground
Reset Button	○	○	Ground
3.3V	○	○	Power Fail LED
UID LED	○	○	OH/PWR Fail/Fan Fail LED
3.3V Stby	○	○	NIC2 Active LED
3.3V Stby	○	○	NIC1 Active LED
3.3V Stby	○	○	HDD LED
3.3V	○	○	PWR LED
X	○	○	X
NMI	○	○	Ground
	19	20	

19

20

**Jumpers, Connectors and LED Indicators**

**Jumpers**

JBT1	CMOS Clear	Open (Normal)
JPL1	LAN1/LAN2 Enable	Pins 1-2 (Enabled)
JPME1	ME Recovery	Pins 1-2 (Normal)
JPME2	Manufacturing Mode (ME) Select	Pins 1-2 (Normal)
JWD1	Watch Dog Timer Enable	Pins 1-2 (Normal)

**Connectors**

Battery (BT1)	Onboard CMOS battery
FAN1~6	System cooling fan headers
IPMI_LAN	Dedicated IPMI LAN port
JAOM	PCI-E 3.0 x16 SAS3 AOM controller slot
JD1	Speaker/buzzer header (optional) ( <b>Note 1</b> )
JF1	Front control panel header
JIPMB1	4-pin external BMC I <sup>2</sup> C header (for an IPMI card)
JL1	Chassis intrusion header ( <b>Note 2</b> )
JM2_1	PCIe M.2 from PCH
JNVI <sup>2</sup> C1/JNVI <sup>2</sup> C2	NVMe SMBus (I <sup>2</sup> C) headers used for PCI-E hot-plug SMBus clock & data connections ( <b>Note 3</b> )
JPI <sup>2</sup> C1	Power Supply SMBus I <sup>2</sup> C header
JPWR1/JPWR2	12V 8-pin power supply connectors
JPWR3	24-pin ATX main power supply connector
JRK1	Intel VROC RAID Key for NVMe SSD
JSDCARD1	Micro SD Card slot
JSTBY1	Standby power header
JTPM1	Port 80 connector for Trusted Platform Module (TPM)
JUIDB1	Unit Identifier (UID) switch
LAN1/LAN2	Gigabit LAN (GLAN) ethernet ports on the back panel
P1_NVME0/1(-NT)	CPU1 NVM Express PCI-E 3.0 x4 ports (Note 4)
P2_NVME0/1 (-NT)	CPU2 NVM Express PCI-E 3.0 x4 ports (Note 4)
(I-)SATA0~3, 4~7	I- SATA 3.0 connectors supported by the PCH
(S-)SATA0~3	S-SATA 3.0 connectors supported by the SCU
(S-)SATA4/S-SATA5	Powered S-SATA connectors w/SuperDOM support

SXB1	PCI-E 3.0 (x16 + x16) Left Riser Card slot
SXB2	PCI-E 3.0 x16 Right Riser Card supported by CPU2
S-SGPIO2	Serial General Purpose I/O port
USB0/1	Back panel USB 3.0 ports
USB2/3	Back panel USB 3.0 ports
USB4/5	USB 3.0 headers
VGA	Back panel VGA port

**LED Indicators**

LE1	UID (Unit Identifier) LED	Solid Blue: Unit Identified
LE2	Onboard Power LED	On: Onboard Power On
LE3	M.2 LED	Blinking Green: Device Working
LEDM1	BMC Heartbeat LED	Blinking Green: BMC Normal

Note: 1. This feature is available when an external speaker/buzzer is used. 2. Please connect a cable from the Chassis Intrusion header at JL1 to the chassis to receive an alert via IPMI. 3. An SMCI-proprietary NVMe add-on card and cable are required; available for a Supermicro complete system only. 4. When installing an NVMe device on a motherboard, please be sure to connect the first NVMe port (P1\_NVME0) first for your system to work properly.

**CPU Support**


This motherboard supports dual Intel Xeon Scalable-SP or 2nd Gen Intel Xeon Scalable-SP series processors (Socket P); each processor supports dual full-width Intel QuickPath Interconnect (QPI) links of up to 10.4GT/s one direction per QPI.

**Memory Support**

This motherboard supports up to 3TB of 3DS LRDIMM, LRDIMM, 3DS RDIMM, RDIMM, NV-DIMM DDR4 (288-pin) ECC 2933/2666/2400/2133 MHz memory modules in 12 slots. (**Notes:** 1. Up to 4TB is supported with (L)RDIMM and DCPMM populated in a balanced memory configuration. 2. 2933 MHz memory is supported by 2nd Gen Intel Xeon Scalable-SP(82xx/62xx) series processors only. 3. Unbalanced memory configuration decreases memory performance and is not recommended.)

Memory Population Table	
When 1 CPU is used:	Memory Population Sequence
1 CPU & 1 DIMM	CPU1: P1-DIMMA1
1 CPU & 2 DIMMs	CPU1: P1-DIMMA1/P1-DIMMD1
1 CPU & 3 DIMMs	CPU1: P1-DIMMC1/P1-DIMMB1/P1-DIMMA1
1 CPU & 4 DIMMs	CPU1: P1-DIMMB1/P1-DIMMA1/P1-DIMMD1/P1-DIMME1
1 CPU & 5 DIMMs (Unbalanced: not recommended)	CPU1: P1-DIMMC1/P1-DIMMB1/P1-DIMMA1/P1-DIMMD1/P1-DIMME1
1 CPU & 6 DIMM	CPU1: P1-DIMMC1/P1-DIMMB1/P1-DIMMA1/P1-DIMMD1/P1-DIMME1/P1-DIMMF1
When 2 CPUs are used:	Memory Population Sequence
2 CPUs & 2 DIMMs	CPU1: P1-DIMMA1/P2-DIMMA1
2 CPUs & 4 DIMMs	CPU1: P1-DIMMC1/P2-DIMMD1/P1-DIMMA1
2 CPUs & 6 DIMMs	CPU1: P1-DIMMC1/P2-DIMMD1/P2-DIMMA1
2 CPUs & 8 DIMMs	CPU1: P1-DIMMB1/P2-DIMMA1/P1-DIMMD1/P2-DIMME1
2 CPUs & 10 DIMMs	CPU1: P1-DIMMC1/P2-DIMMB1/P1-DIMMA1/P1-DIMMD1/P1-DIMME1/P1-DIMMF1
2 CPUs & 12 DIMMs	CPU1: P1-DIMMC1/P2-DIMMB1/P2-DIMMA1/P2-DIMMD1/P2-DIMME1/P2-DIMMF1

**PCI-E M.2 Slot Installation**



**Back Panel I/O Connectors**

