SUPERMICR SuperServer 6019P-WT/WTR Quick Reference Guide

Board Layout



		Front View and Feat	tures
Н	DDO	HDD4 HDD4 HDD1 HDD7	5 1 HDD3
SI	ot	Description	
0~	~3	3.5" Hot-Swap SATA3/SAS3* Drive B	says
4	4	Slim DVD or 2.5" SSD Bay**	
5	5	Slim Floppy or 2.5" SSD Bay**	
		UID & 盘 盘 □ ♡	7
No.		Description	
1		UID Button	
2		Universal Information LED	
3		LAN1 LED & LAN2 LED	
4		HDD LED	
5		Power LED	
6		Reset Button	
7		Power Button	
8		Device Activity LED	
9		Device Status LED	
10		Service/Asset Tag, Pull-out identifier (with BMC ADMIN default password underneath)	
		Deer View and Feet	



1	Single Power Supply Module
2	Redundant Power Supply Modules
3	VGA Port
4	Dedicated IPMI Port
5	USB 3.0 Ports
6	LAN Ports
7	PCI-E 3.0 x8 LP Slot (CPU2)
8	PCI-E 3.0 x16 FHHL Slot (CPU2)
9	PCI-E 3.0 x16 FHHL Slot (CPU1)



ADMIN user

