

SUPERMICRO® SuperServer AS -1123US-TR4 Quick Reference Guide

Board Layout

No.	Description
1	SXB1A/1B/1C: WIO-L Riser Card Support (CPU2 PCI-E 3.0 x16 and CPU2 PCI-E 3.0 x16)
2	SXB2: WIO-R Riser Card Support (CPU2 PCI-E 3.0 x16)
3	JS1: SATA8~11 (SATA 3.0 Ports)
4	JBT1: CMOS Clear
5	SXB3A/3B/3C: Ultra I/O Riser Card Support (CPU1 PCI-E 3.0 x8, CPU1 PCI-E 3.0 x16)
6	SATA0~7, 12, 13 Ports
7	P1-DIMME1~H2 slots
8	CPU1
9	P1-DIMMA1~D2 slots
10	P2-DIMME1~H2 slots
11	CPU2
12	P2-DIMMA1~D2 slots
13	JSD1, JSD2: SATA DOM (Device on Module) power connectors 1/2
14	P1-NVME0/1, P2-NVME0/1: Processor 1 NVMe Ports, Processor 2 NVMe Ports

Memory

Processors and their Corresponding Memory Modules																
CPU#	Channel 1	Channel 2	Channel 3	Channel 4	Channel 5	Channel 6	Channel 7	Channel 8								
8 DIMMS																
CPU1				C2	D2			G2	H2							
CPU2				C2	D2			G2	H2							
16 DIMMS																
CPU1	A2	B2	C2	D2	E2	F2	G2	H2								
CPU2	A2	B2	C2	D2	E2	F2	G2	H2								
32 DIMMS																
CPU1	A1	A2	B1	B2	C1	C2	D1	D2	E1	E2	F1	F2	G1	G2	H1	H2
CPU2	A1	A2	B1	B2	C1	C2	D1	D2	E1	E2	F1	F2	G1	G2	H1	H2

Front View & Interface

***Optional NVMe support from CPU1**

No.	Description
1	Power LED
2	HDD LED
3	NIC1 LED
4	NIC2 LED
5	Information LED
6	Power Button
7	UID button/LED
8	Hard Drive Signal
9	Hard Drive Fail

Rear View

No.	Description
1	2 PCI-E x16 (FH/HL 9.5") Slots
2	PCI-E x8 (LP) Slot
3	VGA Port
4	UID LED
5	Serial Port
6	Dedicated LAN for IPMI
7	2 USB 3.0 Ports
8	4 LAN Ports (Ultra riser card)
9	Redundant Power Supply Modules

*Redundancy based on configuration and application load

CPU Installation

Processor Installation

1. Removing the Processor Force Frame
Use a **Torx T20** driver to loosen the screws holding down Force Frame in the sequence of 3-2-1. The screws are numbered on the Force Frame next to each screw hole.
2. Raising the Force Frame
3. Lifting the Rail Frame
4. Removing the External Cap and PnP Cover Cap
5. Inserting the Carrier Frame/CPU Package
6. Lowering the Force Frame
7. Securing the Force Frame
Secure the screws in the order 1-2-3, tightening to **16.1 kgf-cm (14 lbf-in)** torque. The Force Frame secures both the Rail Frame and CPU Package. Caution: Tightening must be executed in proper 1-2-3 sequence to avoid causing catastrophic damage to the socket or CPU Package.
8. The Force Frame Secured

Hard Drive Installation

Removing a Hot-Swap Drive Carrier from the Chassis

1. Press the release button on the drive carrier, which will extend the drive carrier handle.
2. Use the drive carrier handle to pull the drive out of the chassis.

Installing a Drive

1. Remove the dummy drive, by removing the screws securing the dummy drive to the carrier. These screws are not used to mount the actual hard drive.
2. Insert a drive into the carrier with the PCB side facing down and the connector end toward the rear of the carrier. Align the drive in the carrier so that the screw holes line up.
3. Secure the drive to the carrier with four M3 screws, included in the chassis accessory box.
4. Insert the drive carrier with the disk drive into its bay, keeping the carrier oriented so that the release button is on the right side. When the carrier reaches the rear of the bay, the release handle retracts.
5. Push the handle in until it clicks into its locked position.

Heatsink Installation

1. Mounting the Heatsink
2. Securing the Heatsink
Using a diagonal pattern and a **Torx T20** driver, tighten the four heatsink screws evenly to **16.1 kgf-cm (14.0 lbf-in)** torque.

Caution

SAFETY INFORMATION

IMPORTANT: See installation instructions and safety warning before connecting system to power supply.
http://www.supermicro.com/about/policies/safety_information.cfm

WARNING:

To reduce risk of electric shock/damage to equipment, disconnect power from server by disconnecting all power cords from electrical outlets. If any CPU socket empty, install protective plastic CPU cap

WARNING:

Always be sure all power supplies for this system have the same power output. If mixed power supplies are installed, the system will not operate.

For more information go to : <http://www.supermicro.com/support>

<http://www.supermicro.com>

MNL-1960-QRG

Rev. 1.0b