

# MegaDC SuperServer ARS-111M-NR

1U UP MegaDC with 10 hot-swap 2.5" NVMe drives



More details here

## Key Applications


Enterprise Server, Hyperscale Data Center, Front End Server, Infrastructure,

## Key Features


- Single Socket Ampere® AmpereOne® Processor (Up to 192 Cores) ; Up to 400W TDP;
- 16 DIMMs; Up to 4TB ECC Registered DDR5-5600MHz RDIMM/LRDIMM;
- 3 PCIe 5.0 x16 (LP) Slots, 1 AIOM Slot (OCP3.0 Mezzanine Compatible);
- 2x 25Gb LAN SFP28 Ports via BCM57414 Controller w/NC-SI;
- 10x 2.5" U.2 NVMe Hot-Swap Drive Bays;
- 860W Redundant Titanium Level High-efficiency Power Supplies;
- 1 VGA, 1 (Serial) Micro USB Port, 2 USB3.0 (2 Rear);



<b>Form Factor</b>	<p>1U Rackmount</p> <p>Enclosure: 437 x 43 x 597mm (17.2" x 1.7" x 23.5")</p> <p>Package: 602 x 190.5 x 800.1mm (23.7" x 7.5" x 31.5")</p>
<b>Processor</b>	<p>Single processor(s)</p> <p>Ampere® AmpereOne® processor</p>
<b>System Memory</b>	<p>Slot Count: 16 DIMM slots</p> <p>Max Memory (1DPC): Up to 2TB 5200MT/s ECC DDR5 RDIMM/LRDIMM</p> <p>Max Memory (2DPC): Up to 4TB 4400MT/s ECC DDR5 RDIMM/LRDIMM</p>
<b>Drive Bays Configuration</b>	<p>Default: Total 10 bays</p> <ul style="list-style-type: none"> <li>• 10 front hot-swap 2.5" NVMe drive bays</li> </ul> <p>M.2: 1 M.2 NVMe slot (M-key 2280/22110)</p>
<b>Expansion Slots</b>	<p>Default</p> <ul style="list-style-type: none"> <li>• 3 PCIe 5.0 x16 LP slots</li> <li>• 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)</li> </ul>
<b>On-Board Devices</b>	<p>Chipset: Ampere®</p> <p>Network Connectivity: 1 SFP28 25GbE with Broadcom®</p> <p>2 SFP28 10GbE with Broadcom® (optional)</p>
<b>Input / Output</b>	<p>LAN: 1 RJ45 1 GbE Dedicated BMC LAN port</p> <p>2 SFP28 25 GbE LAN ports</p> <p>USB: 2 USB 3.0 ports(rear)</p> <p>2 USB 2.0 ports(front)</p> <p>Video: 1 VGA port</p> <p>Serial: 1 port</p>



Drive Bay	Description
1 - 10	10 Hot-swap 2.5" NVMe Drive Bays



Slot	Slot Description
1 - 4	PCIe 5.0 x16 LP
5	PCIe 5.0 x16 AOM (OCP 3.0)

System Cooling	Fans: Up to 6 Heavy Duty 4cm Fan(s) Air Shroud: 1 Air Shroud
Power Supply	2x 860W Redundant (1 + 1) Titanium Level (96%) power supplies
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 46 lbs (20.9 kg) Net Weight: 25 lbs (11.34 kg) Available Color: Black front & silver body
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	<a href="#">Super R13SPD</a>
Chassis	<b>CSE-LB16TS-R000AMNFP</b>