

IoT SuperServer AS -E300-14GR-01-G2

Mini-1U Embedded System with AMD EPYC™ 4004/4005 or Ryzen™ 7000/9000 Series Processor up to 65W TDP



Key Applications

Retail Store Appliance

Gold Configuration Details

- CPU: 1x AMD EPYC™ 4545P (16C/3.0GHz)
- Memory: 32GB DDR5-5600
- Storage: 1x 960GB M.2 NVMe SSD
- NIC: 4x 1GbE RJ45
- NIC: 1x dedicated IPMI Port
- Power: 180W Power Adapter




Base System Specs

Form Factor	Fan-based Embedded Enclosure: 264.8 x 43 x 225.8mm (10.43" x 1.69" x 8.89") Package: 381 x 276 x 142mm (15" x 10.87" x 5.59")
Processor	Single Socket AM5 (LGA-1718) AMD EPYC™ 4005/4004 Series Processor 16C/32T; 64MB Cache
System Memory	Slot Count: 4 DIMM slots Max Memory (1DPC): 192GB 5600MT/s ECC/non-ECC DDR5 UDIMM
Drive Bays Configuration	1 M.2 PCIe 5.0 x4 NVMe slot (M-key 2280) 1 M.2 PCIe 5.0 x4 NVMe slot (M-key 22110)
On-Board Devices	AMD B650
Input / Output	LAN: 4 RJ45 1 GbE LAN ports (Intel® I350-AM4) 1 RJ45 1 GbE Dedicated BMC LAN port (ASPEED AST2600) USB: 1 USB 3.2 Gen2 Type-C port(Rear) 2 USB 3.2 Gen2 Type-A ports(Rear) 1 USB 3.2 Gen1 Type-A port(Rear) Video: 1 HDMI 2.1 port(Rear) 1 Mini-DP port(Rear) TPM: 1 TPM header 1 TPM Onboard/port 80

(Front View – System)



(Rear View – System)



Slot	Slot Description
1	PCIe 5.0 x16 LP

System Cooling	Fans: Up to 1 CPU heatsink with 70x70x15mm Fan(s) Up to 2x 4-PIN PWM 40x40x28mm Fan(s)
Power Supply	1x 180W power supply
System BIOS	BIOS Type: AMI 32MB UEFI BIOS Features: ACPI 6.5 SMBIOS 3.7 or later UEFI 2.9
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!; Plug-ins for 3rd Party Software
PC Health Monitoring	FAN: Status monitor for speed control
Dimensions and Weight	Weight: Gross Weight: 7.5 lbs (3.4 kg) Net Weight: 3.7 lbs (1.6 kg) Available Color: Black
Operating Environment	Operating Temperature: 0°C to 40°C (32°F to 104°F) with 0.7 m/s airflow Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super H14SRV-HLN4F
Chassis	CSE-E300