

Storage SuperServer SSG-621E-ACR12L

2U front-loading storage server with 12 hot-swap 3.5" SAS/SATA bays (6 optional NVMe) and PCIe 5.0



More details here

Key Applications

Enterprise Server, iSCSI SAN, HPC, Data Center, Database Processing & Storage, Corporate Database, Appliance Optimized Storage Building Blocks,

Key Features

- Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors;
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s(1DPC) in 16 DIMM slots;
- 2x 10 GbE onboard via Broadcom BCM57416
 - 1x GbE Dedicated LAN for server remote management: IPMI 2.0 / KVM over LAN / Media over LAN;
- 12x 3.5"/2.5" Hot-swap SAS3/SATA3 drives, 2x Rear 2.5" SATA Slots, 2x NVMe M.2 (form factor: 2280 and 22110);
- 3x 8cm hot-swap counter-rotate redundant PWM cooling fans;
- 1200W Redundant Power Supplies Titanium Level (96%);
- HBA Controller support via Broadcom® 3816;




Form Factor	2U Rackmount Enclosure: 437 x 89 x 650mm (17.2" x 3.5" x 25.6") Package: 673 x 292 x 864mm (26.5" x 11.5" x 34")
Processor	Dual Socket E (LGA-4677) 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors
System Memory	Slot Count: 16 DIMM slots Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM
Drive Bays Configuration	<p>Default: Total 14 bays</p> <ul style="list-style-type: none"> • 12 front hot-swap 3.5" SAS/SATA drive bays • 2 rear hot-swap 2.5" SATA drive bays <p>Option A: Total 6 bays</p> <ul style="list-style-type: none"> • 6 front hot-swap 3.5" PCIe 5.0 x4 NVMe* drive bays <p>(*NVMe support may require additional storage controller and/or cables, please see the optional parts list for details)</p> <p>M.2: 2 M.2 PCIe 4.0 x2 NVMe slots (M-key 2280/22110)</p>
Expansion Slots	<p>Default</p> <ul style="list-style-type: none"> • 4 PCIe 5.0 x16 (in x16) LP slots • 2 PCIe 5.0 x8 (in x8) LP slots
On-Board Devices	<p>Chipset: Intel® C741</p> <p>Network Connectivity: 2 RJ45 10GbE with Broadcom® BCM57416</p>
Input / Output	<p>LAN: 1 RJ45 1 GbE Dedicated BMC LAN port 2 RJ45 10 GbE LAN ports (Broadcom® BCM57416) (IPMI shared on LAN port 1)</p> <p>USB: 4 USB 3.0 ports(rear)</p> <p>Video: 1 VGA port(Rear)</p> <p>Serial: 1 COM port(Rear)</p> <p>TPM: 1 TPM header</p>

(Front View – System)



Drive Bay	Description
1 – 8	Hot-swap 3.5" NVMe/SAS3/SATA3 Drive Bays
9 – 12	Hot-swap 2.5" SAS3/SATA3 Drive Bays

(Rear View – System)



Slot	Description
0	PCIe 5.0 x8 (Occupied by S316 SAS Controller)
1	PCIe 5.0 x16
2	PCIe 5.0 x16
3	PCIe 5.0 x8

Drive Bay	Description
60 – 63	Hot-swap 2.5" SATA3 Drive Bays

CPU

CPU2

System Cooling

Fans: Up to 3 Heavy Duty 8cm Fan(s)
 Air Shroud: 1 Air Shroud

Power Supply

2x 1200W Redundant Titanium Level (96%) Hot-plug power supplies

System BIOS

BIOS Type: AMI 32MB SPI Flash EEPROM

Management

SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!

PC Health Monitoring

CPU: Monitors for CPU Cores, Chipset Voltages, Memory
 7+1 Phase-switching voltage regulator
 FAN: Fans with tachometer monitoring
 Status monitor for speed control
 Pulse Width Modulated (PWM) fan connectors
 Temperature: Monitoring for CPU and chassis environment
 Thermal Control for fan connectors

Dimensions and Weight

Weight: Gross Weight: 58 lbs (26.3 kg)
 Net Weight: 34 lbs (15.4 kg)
 Available Color: Black

Operating Environment

RoHS Compliant
 Operating Temperature: 10°C to 35°C (50°F to 95°F)
 Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)
 Operating Relative Humidity: 8% to 90% (Non-Condensing)
 Non-operating Relative Humidity: 5% to 95% (Non-Condensing)

Motherboard[Super X13DEI-T](#)**Chassis**[CSE-826BTS-R1K23LPBP2](#)