

Hyper SuperServer SYS-112H-TN

1U UP Hyper supporting up to 12 hot-swap 2.5" NVMe/SAS/SATA bays and up to 3 PCIe 5.0 + 1 PCIe 5.0 AIOM slots



Key Applications

Virtualization, Financial, Scale Out All-Flash NVMe Storage, Data Center Enterprise Applications, Cloud Computing, AI Inference, CDN/vCDN/Cloud CDN,

Key Features


- Hyper is a flagship performance rackmount server optimized for scale-out cloud workloads.;
- Single Intel® Xeon® 6 Processor.;
- 16 DIMM slots support RDIMM / MRDIMM(1DPC);
- Double width add-on card support.;
- Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible).;
- Breeze through high throughput workloads with PCIe 5.0 NVMe drive support.;
- Trusted Platform Module (TPM) 2.0 onboard.;
- Modularized and Tool-less design for easy serviceability.;



Form Factor	<p>1U Rackmount</p> <p>Enclosure: 437 x 43 x 778.7mm (17.2" x 1.7" x 30.66")</p> <p>Package: 672 x 224 x 1100mm (26.46" x 8.82" x 43.31")</p>
Processor	<p>Single Socket E2 (LGA-4710)</p> <p>Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores</p> <p>P-cores: Up to 86C/172T; Up to 336MB Cache</p> <p>E-cores: Up to 144C/144T; Up to 108MB Cache</p>
GPU	<p>Max GPU Count: Up to 1 double-width or 3 single-width GPUs</p> <p>Supported GPU: NVIDIA PCIe: L4, L40S</p> <p>Intel PCIe: Intel Data Center GPU Flex 170</p> <p>CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect</p>
System Memory	<p>Slot Count: 16 DIMM slots</p> <p>Max Memory (1DPC): Up to 2TB 6400MT/s ECC DDR5 RDIMM</p> <p>Max Memory (1DPC): Up to 512GB 8000MT/s ECC DDR5 MRDIMM</p> <p>Max Memory (2DPC): Up to 4TB 5200MT/s ECC DDR5 RDIMM</p>
Drive Bays Configuration	<p>Default: Total 8 bays</p> <ul style="list-style-type: none"> • 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays <p>Option A: Total 12 bays</p> <ul style="list-style-type: none"> • 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays • 4 front hot-swap 2.5" SAS*/SATA* drive bays <p>Option B: Total 12 bays</p> <ul style="list-style-type: none"> • 12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays <p>(*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details)</p> <p>M.2: 2 M.2 NVMe slots (M-key 2280/22110/25110; VROC required for RAID)</p>
Expansion Slots	<p>Default</p> <ul style="list-style-type: none"> • 1 PCIe 5.0 x16 (in x16) FHHL slot • 1 PCIe 5.0 x16 (in x16) FHFL double-width slot • 1 PCIe 5.0 x16 (in x16) AIOM slot (OCP 3.0 compatible) <p>Option A*</p> <ul style="list-style-type: none"> • 1 PCIe 5.0 x16 (in x16) FHHL slot • 2 PCIe 5.0 x16 (in x16) FHFL slots • 1 PCIe 5.0 x16 (in x16) AIOM slot (OCP 3.0 compatible)
On-Board Devices	<p>NVMe: NVMe; RAID 0/1/5/10 support(Intel® VROC RAID key required)</p> <p>Network Connectivity: Via AIOM</p>
Input / Output	<p>LAN: 1 RJ45 1 GbE Dedicated BMC LAN port</p>

USB: 2 USB 3.2 Gen1 ports(Rear)
1 USB 3.2 Gen1 port(Front)
Video: 1 VGA port

(Front View – System)



Drive Bay	Description
0 - 7	8 Hot-swap 2.5" NVMe/SAS/SATA Drive Bays <small>*NVMe, SAS, or SATA support requires additional parts from the optional parts list</small>

(Front View – System)



Drive Bay	Description
0 - 11	12 Hot-swap 2.5" NVMe/SAS/SATA Drive Bays <small>*NVMe, SAS, or SATA support requires additional parts from the optional parts list</small>

System Cooling	Fans: Up to 8 counter-rotating 40x40x56mm Fan(s) Air Shroud: 1 CPU Air Shroud
Power Supply	2x 1200W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 64MB SPI Flash
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 41.4 lbs (18.8 kg) Net Weight: 19.2 lbs (8.7 kg) Available Color: Silver
Operating Environment	Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super X14SBH
Chassis	CSE-HS101-R000NFP