

# IoT SuperServer SYS-211TP-HPTRD

X13 SuperEdge 2U4-Node UP rear I/O server with 24 SATA bays



More details here

## Key Applications

Multi-Access Edge Computing (MEC), VRAN/ORAN for Telecom, Enterprise Edge,


## Key Features

- Four **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following:;
- Single Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors (per node);
- Intel® C741 Chipset;
- 8 DIMMs; Up to 2TB ECC DDR5-5600MT/s R-DIMM / R-DIMM 3DS (per node);
- 2 PCIe Gen5 x16 HHHL slot (per node);
- 2 NVMe M.2 2280 / 25110 (per node)
- Front hot-swappable 2.5" HDD/SSD tray (6 tray per node);
- 4 heavy duty 8cm PWM fans with optimal fan speed control (Per System);
- 1+1 Redundant 2000W DC Power Supplies (per system);
- Intel® X710 Dual port 10G SFP+ onboard;




Form Factor	2U Rackmount Enclosure: 438 x 88 x 730mm (17.25" x 3.5" x 28.75") Package: 526 x 250 x 965mm (20.7" x 9.8" x 38")
Processor	Single Socket E (LGA-4677) 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors Up to 60C/120T; Up to 300MB Cache
System Memory	Slot Count: 8 DIMM slots/1 Channels Max Memory (1DPC): Up to 2TB 5600MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 6 bays <ul style="list-style-type: none"> <li>• 6 front hot-swap 2.5" SATA drive bays</li> </ul> M.2: 2 M.2 PCIe 5.0 x4 NVMe slots (M-key 2280/22110/25110; VROC required for RAID)
Expansion Slots	Default <ul style="list-style-type: none"> <li>• 2 PCIe 5.0 x16 HHHL slots</li> </ul>
On-Board Devices	SATA: SATA (6Gbps) Chipset: Intel® C741 Network Connectivity: 2 SFP+ 10GbE with Intel® X710-BM2
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port 2 SFP+ 10 GbE LAN ports (IPMI shared on LAN port 1) USB: 2 USB 3.2 Gen1 Type-A ports(rear) Video: 1 VGA port(Rear)

(Front View – System)



(Rear View – System)



## System Cooling

Fans: Up to 4x 8cm heavy duty fans with optimal fan speed control 80x80x38mm Fan(s)  
 Air Shroud: 4 Air Shrouds

## Power Supply

2x 2000W Redundant (1 + 1) power supplies

## System BIOS

BIOS Type: AMI 256MB SPI Flash  
 BIOS Features: RTC (Real Time Clock) Wakeup  
 UEFI 2.8  
 SPI dual/quad speed support  
 Riser Card audio detection support  
 ACPI Power Management 6.4  
 SMBIOS 3.5 or later  
 PCI firmware 4.0

## Management

SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!

## PC Health Monitoring

CPU: Monitors for CPU Cores, Chipset Voltages, Memory  
 FAN: Fans with tachometer monitoring  
 Status monitor for speed control  
 Pulse Width Modulated (PWM) fan connectors  
 Temperature: Monitoring for CPU and chassis environment  
 CPU thermal trip support, PEPI

## Dimensions and Weight

Weight: Gross Weight: 90 lbs (40.8 kg)  
 Net Weight: 70 lbs (31.8 kg)  
 Available Color: Black front & silver body

## Operating Environment

RoHS Compliant  
 Operating Temperature: 0°C to 35°C (32°F to 95°F)  
 Non-operating Temperature: 0°C to 70°C (32°F to 140°F)  
 Operating Relative Humidity: 8% to 90% (non-condensing)  
 Non-operating Relative Humidity: 5% to 95% (non-condensing)

## Motherboard

[Super X13SET-PT](#)

## Chassis

[CSE-217HQ+-R2K03BP4](#)