

GPU A+ Server AS -4125GS-TNRT

DP AMD 4U System with up to 8 PCIe Direct-Connect GPUs



More details here

Key Applications

AI / Deep Learning, Big Data Analytics and AI, High Performance Computing, Engineering/scientific research,

Key Features

- Flexible GPU support: active & passive GPUs
Direct Attached Configuration for up to 8 double width, full length GPUs
8 Hot-Swap Heavy Duty Fans with Optimal Fan Speed Control;
- Dual-Socket, AMD EPYC™ 9004/9005 Series Processors up to 400W TDP;
- Supports up to 24 DIMM Slots, 6000 MT/s 6TB DDR5 memory
(Please check System Memory Section for detail);
- Dual front hot-swap 2.5" SATA + 4 front hot-swap 2.5" NVMe drive bays
One onboard M.2 Slot
(The PCIe signal for 4 NVMe drives can be re-directed for PCIe slot8 enablement);
- Total of 4x 2000W Redundant (2+2 or 3+1) Titanium Level power supplies
(2+2 under 4000 Watt, 3+1 under 6000 Watt)
(Power supply full redundancy based on configuration and application load);



Form Factor	4U Rackmount Enclosure: 437 x 178 x 737mm (17.2" x 7" x 29") Package: 685 x 675 x 1041mm (27" x 26.57" x 41")
Processor	Dual processor(s) AMD EPYC™ 9004/9005 Series Processors (* AMD EPYC™ 9005 Series drop-in support requires board revision 2.x) Up to 160C/320T; Up to 512MB Cache per CPU
GPU	Max GPU Count: Up to 8 double-width GPUs Supported GPU: NVIDIA PCIe: H100, H100 NVL, A16, A30, A40, L4, L40S, RTX 6000 Ada Generation, A100, RTX A5000, RTX A6000, RTX A5500, L40, RTX 4000 Ada Generation, RTX 4000 SFF Ada Generation, RTX 4500 Ada, RTX 5000 Ada, NVIDIA RTX PRO™ 6000 Blackwell Max-Q Workstation Edition, RTX A4000 AMD PCIe: Instinct™ MI210, Instinct™ MI100 CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: NVIDIA® NVLink™ Bridge (optional), AMD Infinity Fabric™ Link (optional)
System Memory	Slot Count: 24 DIMM slots Max Memory (1DPC): Up to 6TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor) Max Memory (1DPC): Up to 6TB 6000MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor)
Drive Bays Configuration	Default: Total 6 bays <ul style="list-style-type: none"> • 2 front hot-swap 2.5" SATA drive bays • 4 front hot-swap 2.5" NVMe drive bays Option A: Total 2 bays <ul style="list-style-type: none"> • 2 front hot-swap 2.5" SATA drive bays M.2: 1 M.2 PCIe 3.0 x4 NVMe slot (M-key)
Expansion Slots	Default <ul style="list-style-type: none"> • 9 PCIe 5.0 x16 FHFL slots Option A <ul style="list-style-type: none"> • 10 PCIe 5.0 x16 FHFL slots
On-Board Devices	SATA: SATA (6Gbps) Chipset: AMD SP5 Network Connectivity: 2 RJ45 10GbE
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port 2 RJ45 10 GBASE-T LAN ports

USB: 2 ports(rear)

Video: 1 VGA port

Serial: 1 COM port(rear)

(Front View – System)




Front Panel

Drive Bay		Description
1	2	4 Hot-swap 2.5" NVMe Drive Bays
3	4	2 Hot-swap 2.5" SATA Drive Bays*
5	6	Hot-swap 2.5" SATA Drive Bays* (optional)

*Requires optional RAID controller

(Rear View – System)



Slot Description	
1	PCIe 5.0 x16 (FHF/L)
2	PCIe 5.0 x16 (FHF/L)
3	PCIe 5.0 x16 (FHF/L) - optional based on NVMe configuration

*Full redundancy based on configuration and application load.

CPU

CPU

System Cooling

Fans: Up to 8 heavy duty fans with optimal fan speed control

Power Supply

4x 2000W Redundant (3 + 1) Titanium Level (96%) power supplies

System BIOS

BIOS Type: AMI 32MB SPI Flash EEPROM

Management

SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!

PC Health Monitoring

CPU: Monitors for CPU Cores, Chipset Voltages, Memory

7 +1 Phase-switching voltage regulator

FAN: Fans with tachometer monitoring

Status monitor for speed control

Pulse Width Modulated (PWM) fan connectors

Temperature: Monitoring for CPU and chassis environment

Thermal Control for fan connectors

Dimensions and Weight

Weight: Gross Weight: 100 lbs (45.3 kg)

Net Weight: 65.5 lbs (29.7 kg)

Available Color: Black Front & Silver Body

Operating Environment

Operating Temperature: 10°C to 35°C (50°F to 95°F)

Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)

Operating Relative Humidity: 8% to 90% (non-condensing)

Non-operating Relative Humidity: 5% to 95% (non-condensing)

Motherboard[Super H13DSG-O-CPU](#)**Chassis**

CSE-418G2TS