

CloudDC SuperServer SYS-121C-TN2R

1U DP CloudDC with 8 hot-swap 2.5" SATA (2 NVMe hybrid) bays and 2 PCIe 5.0 x16 slots + 2 PCIe 5.0 x16 AIOM slots



Key Applications


Web Server, Firewall Application, Data Center Optimized, Value IaaS, Cloud Computing, Compact Server, DNS & Gateway Servers, Firewall Application, CDN, Edge Nodes,

Key Features

- Dual sockets E (LGA-4677) 5th and 4th Gen Intel® Xeon® Scalable processors;
- 16 DIMMs up to 4TB 3DS ECC DDR5-5600: RDIMM;
- 2 PCIe 5.0 x16 FHHL; 2 PCIe 5.0 x4 NVMe M.2;
- Dual AIOM (OCP 3.0) slots with NCSI for networking, 1 dedicated IPMI LAN;
- 8x 2.5" hot-swap SATA/SAS4 w/ 2x hybrid NVME drive bays;
- 1 VGA, 1 COM, 2 USB 3.0 (rear);



Form Factor	1U Rackmount Enclosure: 437 x 43 x 597mm (17.2" x 1.7" x 23.5") Package: 605 x 197 x 822mm (23.8" x 7.8" x 32.4")
Processor	Dual Socket E (LGA-4677) 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors Up to 36C/72T; Up to 82.5MB Cache per CPU
GPU	Max GPU Count: Up to 2 single-width GPUs Supported GPU: NVIDIA PCIe: L4, A2 Intel PCIe: Intel Data Center GPU Flex 140
System Memory	Slot Count: 16 DIMM slots Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 8 bays • 2 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays • 6 front hot-swap 2.5" SAS*/SATA* drive bays (*NVMe/SAS/SATA support may require additional storage controller and/or cables) M.2: 2 M.2 PCIe 5.0 x4 NVMe slots (M-key 2280(default); VROC required for RAID) Peripheral Bays: 1 slim DVD bay (optional)
Expansion Slots	Default • 2 PCIe 5.0 x16 FHHL slots • 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)
On-Board Devices	SATA: SATA (6Gbps) ; RAID 0/1/5/10 support NVMe: NVMe; RAID 0/1/5/10 support(VROC HW key required) Chipset: Intel® C741 Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.2 Gen1 Type-A ports(rear) Video: 1 VGA port Serial: 1 COM port(Rear) TPM: 1 TPM header



System Cooling	Fans: Up to 6x 4cm heavy duty fans with optimal fan speed control Air Shroud: 2 Air Shrouds
Power Supply	2x 860W Redundant (1 + 1) Titanium Level (96%) Hot-plug power supplies
System BIOS	BIOS Type: AMI 32MB SPI FLASH ROM
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors CPU: Monitors for CPU Cores, Chipset Voltages, Memory. 8 Phase-switching voltage regulator
Dimensions and Weight	Weight: Gross Weight: 40 lbs (18.1 kg) Net Weight: 25 lbs (11.3 kg) Available Color: Black front & silver body
Operating Environment	RoHS Compliant Name: A2 Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -30°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 80% (max 21° DP; non-condensing) Non-operating Relative Humidity: 8% to 90% (max 38° DP; non-condensing)
Motherboard	Super X13DDW-A
Chassis	CSE-LB13TS-R0AWNP2