

BigTwin SuperServer SYS-220BT-HNC8R-US



2U BigTwin with 6 2.5" NVMe/SAS/SATA drives per node (Made in USA)

More details here

Key Applications


Container-as-a-Service; Application Accelerator, Diskless HPC Clusters, All-Flash Hyperconverged Infrastructure,

Key Features

- Four **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following:;
- Socket P+ (LGA 4189) support 3rd Gen Intel® Xeon® Scalable processors;
- Intel® C621A;
- 20 DIMM Slots (16 DIMM Slots + 4 Intel® Optane™ Persistent Memory Slots);
- 2 PCIe 4.0 x16 (LP) slot; Tool-less support
Optional HW RAID Boot Controller via AOC-SMG3-2M2-B (NVMe Only)
Internal PCIe 3.0 for 2 x4 M.2 NVMe/SATA support onboard;
- Network connectivity via AIOM (OCP 3.0 compliant);
- 6 Hot-swap 2.5" drive bays; 6 PCIe 4.0 NVMe/SAS/SATA 2.5" drives;
- 4 cooling fans per 2U enclosure, 16.5K RPM; Shared Cooling Design;
- 2600W Redundant Power Supplies Titanium Level (96%+); Shared Power Design;
- Built-in SAS3 Support via Broadcom 3808; IT Mode;



| | |
|--------------------------|--|
| Form Factor | 2U Rackmount Enclosure: 449 x 88 x 730mm (17.68" x 3.47" x 28.75") Package: 626 x 248 x 1150mm (24.65" x 9.76" x 45.28") |
| Processor | Dual Socket P+ (LGA-4189) 3rd Gen Intel® Xeon® Scalable processors Up to 36C/72T; Up to 54MB Cache per CPU |
| System Memory | Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM Supports Intel® Optane™ persistent memory 200 series |
| Drive Bays Configuration | Default: Total 6 bays <ul style="list-style-type: none"> • 6 front hot-swap 2.5" PCIe 4.0 NVMe/SAS/SATA drive bays • 2 M.2 PCIe 3.0 x4 NVMe/SATA slots (M-key 2280(default); VROC required for RAID) |
| Expansion Slots | Default <ul style="list-style-type: none"> • 2 PCIe 4.0 x16 LP slots |
| On-Board Devices | Chipset: Intel® C621A Network Connectivity: Via AIOM |
| Input / Output | LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 Type-A ports(Rear) Video: 1 VGA port |



System Cooling Fans: Up to 4x 16.5K RPM Heavy Duty 8cm Fan(s)
Air Shroud: 4 Air Shrouds

Power Supply 2x 2600W Redundant (1 + 1) Titanium Level (96%) power supplies

System BIOS BIOS Type: AMI 32MB Flash ROM

Management SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!

PC Health Monitoring FAN: Fans with tachometer monitoring
Status monitor for speed control
Pulse Width Modulated (PWM) fan connectors
Temperature: Monitoring for CPU and chassis environment
CPU: Monitors for CPU Cores, Chipset Voltages, Memory.
7+1 Phase-switching voltage regulator

Dimensions and Weight Weight: Gross Weight: 96.6 lbs (43.8 kg)
Net Weight: 66.1 lbs (30 kg)
Available Color: Black front & silver body

Operating Environment RoHS Compliant
Operating Temperature: 10°C to 35°C (50°F to 95°F)
Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)
Operating Relative Humidity: 8% to 90% (Non-Condensing)
Non-operating Relative Humidity: 5% to 95% (Non-Condensing)

Motherboard [Super X12DPT-B6](#)

Chassis CSE-217BQ-000NP