IPMI Firmware Release Notes

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Duade at Name	VAOCDI E
Product Name	X10SRL-F
Release Version	3.90
Build Date	7/17/2020
Previous Version	3.86
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	N/A
New features	N/A
Fixes	1. System now shows as Critical when PSU sensor is not plugged in.
	2. Clear destination address after factory default.
	3. Corrected display of table when the Maintenance Event Log is full and the
	event log has "Activate_BIOS_Product_Key".
	4. Allow patching SSH Port to an already existing/default port value in
	Redfish.
	5. Allow patching Active Directory Role Group Domain with a period in
	Redfish.
	6. Corrected mismatch FRU values "13," "18," and "19" Chassis Type
	between SMCIPMITool FRU and IPMI Web FRU.
	7. Corrected issues with KVM console.
	8. AOC SAS sensor no longer disappears from IPMI sensor reading.
	9. Corrected destination address after updating firmware by SMCIPMITool.