IPMI Firmware Release Notes

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X11SSA-F/ X11SSI-LN4F
Release Version	1.63
Build Date	9/4/2020
Previous Version	1.58
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	N/A
New features	N/A
Fixes	1. Implemented security fix.
	2. Fixed problem of unmount button remaining clickable after
	unmounting on Floppy Disk page.
	3. Fixed failure to enable the upload button after unmounting device
	on Floppy Disk page.
	4. Fixed problem of garbage value showing on Users page.
	5. Fixed malfunction of Power Control Operations and failure of
	"power on" function via UI page.

6. Fixed inability to restore some settings after reloading saved IPMI
Configuration file.
7. Fixed inconsistency of prompt message after deleting Group Name
of AD.

1.58 (11/20/2019)

- 1. Added BMC firmware solution to program and store unique pre-programmed password.
- 2. Fixed inability to connect to IPMI Web after updating firmware by IPMIView.
- 3. Fixed failure of Automation Robot.
- 4. Fixed problem of IPMI execution exception occurring when performing a BIOS update.

1.56 (8/30/2019)

- 1. Fixed multiple vulnerabilities with Supermicro BMC Virtual Media.
- 2. Fixed ability of User Network Privilege to stay in Syslog page.
- 3. Fixed issue with IPMI web formatting for system.
- 4. Fixed inability to set Hostname back to empty field.
- 5. Fixed failure of Java iKVM virtual media mount authentication.
- 6. Fixed centering of new date/firmware during IPMI WebGUI BIOS/IPMI firmware update.
- 7. Set Port # to 389 when LDAP Authentication is enabled.
- 8. Fixed inability to close pop-up window, problem of pop-up window showing incorrect information once an invalid Port # is entered, and problem of inputting an invalid Port under Port configuration locking user in an infinite loop of pop-up messages until refreshing.
- 9. Fixed failure of STAC Redfish automation test.
- 10. Fixed ability of RADIUS to set port to an invalid value.
- 11. Fixed ability of Active Directory to input invalid group domain.
- 12. Fixed ability of Active Directory to save blank Domain Controller Server Address IP.
- 13. Fixed ability of NTP Server to input invalid values for both Primary NTP Server and Secondary NTP Server.
- 14. Fixed ability of Alert to input invalid Destination IP.
- 15. Fixed ability of SNMPV3 to save an invalid Auth Key and Private Key, and SNMPV3 to save an invalid User Name.

1.54 (4/16/2019)

- 1. Added patch for CVE-2019-6260 pantsdown.
- 2. Migrated the IPMI Event Log to the URL "redfish/v1/Systems/1/LogServices" in Redfish and changed the name "Event Log" to "Health Event Log" in Redfish and Web UI.
- 3. Set the MAC address format to revert to "xx:xx:xx:xx:xx" in order to prevent backward compatibility.
- 4. Changed FirmwaveInventory to SmcFirmwaveInventory to prevent user confusing with Redfish standard definition.
- 5. Added parameter (SkipCheckingME) for BIOS EnterUpdateMode in Redfish to skip ME checking.
- 6. Added support for TaskService feature during BIOS, BMC, and Broadcom storage controller update in Redfish.
- 7. Added new feature for GUID/BoardID in Redfish.
- 8. Added new feature for event data extension in Redfish.
- 9. Fixed failure of Redfish API test, failure of Redfish Automation tool check, inability of /redfish/v1/Managers/1/VM1/CfgCD/Actions/ path to match URI path, and inability to retrieve memory information from Redfish (postman).
- 10. Fixed failure of Nagios test.

1.48 (6/15/2018)

- 1. Added Redfish memory information feature.
- 2. Fixed problem of the help page of iKVM/HTML5 console not supporting multi-language content and only supporting English.
- 3. Fixed timeout of Invalid Default Active Directory.
- 4. Fixed failure of Redfish automation test.