

IPMI Firmware / BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

| | |
|-------------------------|--|
| Product Name | H12SSW-iN/NT (All) |
| Release Version | 3.10.13 |
| Release Date | 01/29/2021 |
| Previous Version | 3.10.09 |
| Update Category | Critical |
| Dependencies | N/A |
| Important Notes | ECO #25169 IPMI Image SMT_H12AST2500_64M_31013_V.bin Please update IPMI with attached Flash Utility in package. |
| Enhancements | N/A |
| New features | N/A |
| Fixes | AOC Card Thermal reading issue |

Release Notes from Previous Release(s) – these will be appended at the bottom of the current release notes in italic and in smaller print

Rev. 3.10.09 (2020/11/17)

1. Fixed AMD platform NVMe can't get CPLD version when use system bus to probe.
2. Fixed the ikvm reset causes the remote console to disconnect.
3. fixed the MB has an issue which 'Event Log' at IPMI SEL screen is overlapped with 'Keyword Search'
4. Fixes [BIOS Setup menu] IPMI - BMC Network Configuration/IPv6 Support did not restore to default setting "Enable" but disable, while flashing BMC via BMC WebUI w/o check Preserve Config items until press F3 to load default.
5. Fixed the system status always shows critical on IPMI Web.
6. Add the NVMe temperature rules for d4 command.

Rev. 3.10.04 (2020/06/12)

1. Add Kioxia NVMe SSD support.
2. Support CX653106A via PLDM->MCTP->SMBUS.
3. Modify the NVMe controller's API to apply the first and second generation CPLD register tables.
4. Enhancement All platform support BRCM 3008 series.
5. Support AMD GPU MI50.
6. Modify the Redfish PATCH method at "/Systems/1/Bios" and "/Systems/1/Bios/SD" to allow updating of BIOS attributes.
7. Update for NCSI 100G patch
8. Remove all fan running 40% under idle mode.
9. Filter out abnormal values of VRM sensors especially 0xFF.
10. DCMI power reading Improvement.
11. Support x710 over PLDM->MCTP->SMBUS.
12. Modify Fan speed limit.
13. Fixes Some IPMI page display is abnormal with IE browser.
14. Fixes [SMCIPMITools V2.23.x] got fail result via smstc (TC 131 ipmi oem x10cfg ddns..)
15. Fixes [SSM 3.2.x] IPMI security issue: Fail to login the hostname w/ " _ " char via IPMIweb but it still can capture the screenshot via IPMIweb for the SSM/OS deploy-fail test

Rev. 3.09.02 (2019/12/16)

1. IPMI supports the commands required by SPM in the ROME CPU.
2. Improved ADMIN password is incorrect after reloading IPMI configuration
3. Fixes PBID# 103696; smcipmitools V2.23.x; get fail output w/ command "ipmi lan protocol 1"
4. Fixes PBID# 103796 Power on system onboard buzzer still beep when after trigger thermal trip event
5. Fixes PBID# 103724 Redfish automation test fail. ; PBID# 104114 Redfish SATC failed

Revision 3.03 (2019/06/13)

First release.

| |
|--|
| |
|--|