

BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X12DDW-A6
Release Version	1.1b SPS: 4.4.4.58
Build Date	9/18/2021
Previous Version	1.1a
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	1. Enabled 2U non-NVMe system support with 668 RSC.
New features	N/A
Fixes	N/A

Release Notes from Previous Release(s)

1.1a (8/18/2021)

1. Updated 5.22_WhitleyCrb_OACMS_ICX_067 Intel BKCWW32 2021 PV MR5.
2. Updated Dx/Mx microcode from Intel-Generic-Microcode-20210701_NDA.
3. Updated SATA/sATA EFI driver to VROC PreOS v7.6.0.1012.
4. Fixed failure of SUM Test case 254 SecureEraseDisk test.
5. Added support for SUM upload/delete HTTPS TLS certificate.
6. Changed "Hard Drive Security Frozen" default setting to disabled.
7. Prevented system entering to BIOS recovery mode when implanting runtime OA 2.0 software license key under EFI shell on the system that enables chain of trust for Intel boot guard (POST F2->07 and shutdown).
8. Applied workaround for system hang at 68 during cburn power cycle long run.
9. Fixed iPX E GPF when Redfish HI is disabled.
10. Set TOKEN "Sum_UploadTlsKey_SUPPORT" default to enabled to support SUM upload/deletion of HTTPS TLS certificate.
11. Added support for SmcRedfishHostInterface EUI-48 Locally Administered MAC Address.
12. Added support for RSC-D2-666.
13. Added support for BPN-SAS3-LB16A-N10 rev. 2.00.
14. Patched X550 drop issue for dual chip AIOM.
15. Fixed inability to modify NumLock item by SmcPostHotKey.sd.
16. Fixed failure of SUM TC 221 when installing multiple NICs on system.
17. Fixed inability to preserve SGX settings after updating BIOS.
18. Fixed PSOD of VMWare with TPM.
19. Fixed problem of the system hanging during POST when building BIOS with the token "SMC_SETUP_STYLE" as 0.
20. Fixed malfunction of Patrol Scrub on Dx ICX.

1.1 (4/20/2021)

1. Set default Boot Guard profile to 5.
2. Set all OPROM control items to Legacy when boot mode is set to Dual.
3. Updated CPLD Signature table 101 and tool to 1.30.24 for CPLD Signature table 101.
4. Added support for 6+4 NVMe solution.
5. Added new CPU power spec profiles.
6. Fixed problem of T-states always showing 15 levels even when T-state is disabled.
7. Fixed missing offboard output in Setup if limited to 4G in Non-EFI mode.
8. Fixed failure of Microsoft HLK certification and TPM 2.0 UEFI Preboot Interface Test on Microsoft Server 2019.
9. Fixed problem with a CPU exception.
10. Fixed failure to hide the SmcSecureErase setup page when no HDD devices are plugged in.
11. Corrected display of UEFI OS boot option name in BIOS setup.
12. Fixed inability to upload all OOB files on the first BMC boot.
13. Corrected iSCSI Configuration page.
14. Set DIMM size to recalibrate when rank is disabled.

1.0b (3/3/2021)

1. Updated BKCWW09 2021 (PCIe recipe 3.8).
2. Updated Intel-Generic-Microcode-20210226a_NDA and Intel AE.
3. Updated ASPEED VBIOS and EFI driver to 1.11.03.

4. Updated SATA/ssATA EFI driver to VROC PreOS v7.5.0.1152.
5. Kept value of setup string of Manufacturer and Product according to priority "modification of AmiBcp, FUR1, and then SMBIOS Table".
6. Added code to stop AFU support.
7. Added HCC Mx stepping CPU check for CPU stepping display.
8. Automatically disabled and hid ADDDC with x8 width DIMM.
9. Set "NVMe Firmware Source" to auto-hide when AOC-SMG3-2M2-B is plugged in.
10. Disabled MCTP for M.2 slots to prevent system hang with Micron 2300.
11. Removed 4G limit of Intel LAN memory if boot mode is not legacy.
12. Automatically disabled and grayed out ADDDC, UMA-Base Clustering, and mirror mode and enabled NUMA when SGX is enabled.
13. Enhanced SMCI HDD Security feature.
14. Extended memory DIMM serial number information (Samsung, Micron, Hynix).
15. Enhanced SMC DCPMM feature.
16. Added RSC-D2-666-G4 and RSC-D2R-666-G4.
17. Fixed failure of SUT to prompt "Enter User password" screen after setting a password when plugging in SED device.
18. Corrected display of IPv4 address source status after updating BIOS.
19. Fixed missing SMBIOS type 17 BPS information when plugged in at P1-DIMMC2 or P2-DIMMC2.
20. Corrected location of RT UECC log.
21. Fixed failure of RT UECC to be mapped out.
22. Fixed problem of BIOS initialization showing IPV6 address when IPV6 is disabled in the IPMI GUI.
23. Filtered Dynamic HDD Security pages to patch failure of SUM ChangeBiosCfg.
24. Fixed GPU sensor issue with 2U riser.

1.0a (1/4/2021)

1. Updated Intel BKC to WW51 PC2.
2. Added retraining for X550 AIOM link drop.
3. Added F1 reboot function after 3 password attempts.
4. Added NVMe VMD auto mode with enabled VMD when VROC key is present and disabled VMD when VROC key is absent.

Product Manager

Date