

IPMI Firmware Release Notes

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	B1SL1-F/HF and B1SA4-2550F/2750F
Release Version	3.72
Build Date	11/13/2019
Previous Version	3.50
Update Category	Critical
Dependencies	None
Important Notes	None
Enhancements	<ol style="list-style-type: none">1. Hardened Redfish to prevent returning 500 error codes.2. Strengthened web session ID.3. Improved web CSRF security protection.4. Protected DDNS setting from potential web attack by malware.5. Implemented checking bounds of stack buffer to prevent ROP chain attack.
New features	<ol style="list-style-type: none">1. Disable VM unplug button on Java iKVM applet if ISO or IMA is mounted via WebUI.2. Added support for VM Security patch.3. Set all IPv4/IPv6 addresses to display on the sys_info page.4. Added Java KVM text copy and paste.5. Added support for unique pre-programmed default password.6. Added KCM privileges.7. Added information about BMC location, MidPlane product name, and serial number via CMM.
Fixes	<ol style="list-style-type: none">1. Allow launching HTML5/JavaKVM through CMM.2. Allow spaces for username and password in webUI.3. Allow mounting Virtual Media images after changing VM port more than 4 times during Web virtual media mount.4. Corrected response of setting via in-band interface after setting SMTP sender email.5. Corrected Watchdog setting the pre-timeout NMI interruption after counting

	<p>down to pre-timeout interval.</p> <p>6. Prevent the system from triggering “IPMI Virtual CDROM Image function is wrong.”</p> <p>7. Setting ServiceEnable of IPAccessControl via Redfish no longer returns HTTP status code 302.</p> <p>8. Corrected issue with WebUI LDAP SSL setting.</p> <p>9. Redfish/v1/Managers/1/VM1/CfgCD no longer shows plaintext password.</p> <p>10. Blade status no longer stuck at Initializing.</p> <p>11. Corrected communication issue between BMC and CMM.</p> <p>12. Corrected formatting when logging in with long AD name.</p> <p>13. Corrected DIMM information under hardware information of WebGUI.</p> <p>14. Improved DCMI power reading request.</p> <p>15. Allow SMCIPMITool to set IPv6.</p> <p>16. Clear power/temperature records after factory default.</p> <p>17. Corrected sensor reading under CMM view through SMCIPMITOOL.</p> <p>18. SMCIPMITOOL can perform mel download after clearing mel.</p> <p>19. Allow restoring alert configuration.</p> <p>20. Allow CMM to show node maintenance event log.</p> <p>21. Patched pantsdown security fix.</p> <p>22. Match EVENT SEVERITY to Warning alerts.</p> <p>23. Corrected LDAP configuration setup workflow.</p> <p>24. Improved SOL functionality.</p> <p>25. Changed 'event log' to 'health event log' and 'system event log' to 'maintenance event log'.</p> <p>26. Correct maintenance event log setting behavior after IPMI reboots.</p> <p>27. Corrected Web Sort function showing abnormal data for sensor reading.</p> <p>28. Removed HTML Injection in web input fields.</p> <p>29. Corrected XSS cookie attacks.</p>
--	--