

IPMI Firmware Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	H12DGO-6
Release Version	1.00.40
Build Date	10/20/2021
Previous Version	1.00.37
Update Category	Recommended
Dependencies	BIOS v2.1a
Important Notes	ECO #25938 IPMI image: BMC_H12AST2600-ROT-2201MS_20211020_01.00.40_STDsp.bin IPMI Update package: BMC_H12AST2600-ROT-2201MS_20211020_01.00.40_STDsp.zip
Enhancements	N/A
New features	N/A
Fixes	1. Fixed issue of CPU reported overheat message in IPMI event log. 2. Fixed issue of anonymous account or null value can be created on X11 and X12. 3. Fixed issue of buffer overflow in ipmi_lan ASF protocol. 4. Fixed issue of resolv.conf won't be deleted, it may cause a potentially DNS Hijacking. 5. Fixed issue of event log of "Pump Fan" was recorded on an air-cooling system. 6. Fixed issue of BMC NTP Mode 6 Scan.

Release Notes from Previous Release(s)

1.00.37 (07/27/2021)

1. Added support for AST2600 A3 chip.
2. Added threshold and hot-plug events of the pump to SEL.
3. Fixed failure to update motherboard CPLD firmware.
4. Fixed issue of factory default options list disappearing during restore period.
5. Fixed missing GUP1-GPU8 temperature details when exporting to Excel file.
6. Fixed inability of Web page to reconnect correctly after factory default.
7. Fixed issue of BIOS update through WebGUI hanging when IPMI firmware 1.00.36 is being upgraded.
8. Fixed issue of Event log due to "Pump Fan" occurring on an air-cooling system.

1.00.34 (05/06/2021)

9. Improved the PSU tab's status and information display on the sensor reading page.
10. Improved the fan tab's status and information display on the sensor reading page.
11. Changed the maximum number of items that can be displayed on the "Network AOC" tab of the sensor reading page from 10 to 12.
12. Added the Totol_Power item in the SDR list according to the requirements of Form 299.
13. Added new "Network AOC" tab.
14. Corrected BMC events for PSU behavior.
15. Fixed issue of plugging out/in AC power cable getting [CPU1 Temp] event log.
16. Fixed abnormal behavior after turning off "Failed Login Lockout Control".
17. Corrected readings of PSU and power consumption in IPMI WebGUI.
18. Fixed problem of PSU FRU dropping during ON/OFF test.
19. Fixed issue of "AOC_NICx Temp" displaying as 255 degrees C.

1.00.30 (03/29/2021)

1. Corrected readings of PSU and power consumption in IPMI WebGUI.
2. Fixed issue of AOC_NIC temperature sensor reading showing as 255.

1.0.26 (03/05/2021)

1. Disabled pump sensor.
2. Updated the IPMI sensor threshold in order to adapt to the unique floating voltage of AMD CPU.
3. Grouped HGX sensors to reduce the consumption of sensor numbers.
4. Bonded add-on card NIC number to physical PCIe slot.
5. Fixed issue of PSU FRU dropping during ON/OFF test.
6. Fixed missing BIOS backup and golden images in the IPMI WebGUI inventory.
7. Fixed problem of drive FANs reaching full speed when system powers on.
8. Set CPLD register 0x1C based on PSU type to fix CPU/GPU throttle issue.
9. Corrected fan curve of M2 NVMe.
10. Corrected fan curve of U2 NVMe that could lead to duty fluctuating.
11. Fixed missing STD-18380 issue Radius server IP after reloading IPMI configuration file.
12. Corrected the RPM value of the CPU pump.

1.00.21 (12/18/2020)

1. Added cold plate pump information for liquid cooling configuration.
2. Corrected LED status for dedicated LAN.
3. Fixed issue of ID 0xa0 appearing in Maintenance Event Log occasionally.
4. Fixed malfunction of Virtual Media CD-ROM mounting with IPv6.
5. Set inlet temperature sensor offset to reflect actual ambient temperature.
6. Fixed missing temperature reading for MLX card on IPMI.

7. Fixed issue of negative Inlet Temp reading appearing incorrectly in IPMI WebGUI.
8. Changed FPGA Temp parameter arg1 for FPGA version 2.A5 to follow newer specifications and prevent inability of IPMI to read the temperature of the FPGA.

1.00.16 (11/04/2020)

First release.