BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X12DPFR-AN6
Release Version	1.1b SPS 4.4.4.58
Build Date	11/20/2021
Previous Version	1.0a
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	 Updated 5.22_WhitleyCrb_OACMS_ICX_069 Intel BKCWW39 2021 PV MR7 Updated Dx/Mx microcode from Intel-Generic-Microcode-20210927_NDA. Disabled EFI iSCSI support. Enhanced DMI type 42 to support EUI-48. Now supports EUI-48 Locally Administered MAC Addresses. Turned on Shutdown Suppression and Log MCA IERR to fix crash dump error. Changed the default setting of PPR from "Enabled" to "Disabled". Changed string "VMX" to "Intel Virtualization Technology".
New features	N/A
Fixes	 Fixed issue where COM port resource can't be changed, and item's function fails. Fixed clear bits of IPMI CMD 30_A0_15 according to usage of
	location instead of all bytes. 3. Fixed the SMBIOS event log ERROR CODE not displaying correctly under BIOS menu issue (EFI error type). 4. The grayed-out setup item "Lockdown Mode" has been fixed.
	5. Fixed MMCFG base system hang issue.

BIOS Release 1.1a SPS: 4.4.4.56, Build Date: 9/1/2021

- 1. Updated 5.22 WhitleyCrb OACMS ICX 067 Intel BKCWW32 2021 PV MR5.
- 2. Updated Dx/Mx microcode from Intel-Generic-Microcode-20210804 NDA.
- 3. Updated SmcOOB module to 1.01.24 to support SUM clean SMBIOS Event log through BiosCfg header flag.
- 4. Updated riser card string on SMBIOS type 9.
- 5. Set default Boot Guard profile to 5.
- 6. Updated ASPEED VBIOS and EFI driver to 1.11.03.
- 7. Kept value of setup string of Manufacturer and Product according to priority "modification of AmiBcp, FRU1, and then SMBIOS Table".
- 8. Added code to stop AFU support.
- 9. Added HCC Mx stepping CPU check for CPU stepping display.
- 10. Automatically disabled and hid ADDDC with x8 width DIMM.
- 11. Removed 4G limit of Intel LAN memory if boot mode is not legacy.
- 12. Automatically disabled and grayed out ADDDC, UMA-Base Clustering, and mirror mode and enabled NUMA when SGX is enabled.
- 13. Enhanced SMCI HDD Security feature.
- 14. Extended memory DIMM serial number information (Samsung, Micron, Hynix).
- 15. Enhanced SMC DCPMM feature.
- 16. Set all OPROM control items to Legacy when boot mode is set to Dual.
- 17. Updated CPLD Signature table 101 and tool to 1.30.24 for CPLD Signature.
- 18. Corrected the length of riser card string dynamic update for SMBIOS type 9 slot.
- 19. Escalated UNCA error.
- 20. Modified Me version strings and removed the "Manufacturer ID" string.
- 21. Corrected firmware version and vendor on Trusted Computing page.
- 22. Corrected display of IPv4 address source status after updating BIOS.
- 23. Corrected location of RT UECC log.
- 24. Fixed failure of RT UECC to be mapped out.
- 25. Enabled unprogrammed AOC to be plugged in without causing endless restarts.
- 26. Corrected display of IPv6 when IPv6 status is not active.

- 27. Filtered Dynamic HDD Security pages to patch failure of SUM ChangeBiosCfg.
- 28. Fixed problem of T-states always showing 15 levels even when T-state is disabled.
- 29. Fixed problem with a CPU exception.
- 30. Fixed failure to hide the SmcSecureErase setup page when no HDD devices are plugged in.
- 31. Corrected display of UEFI OS boot option name in BIOS setup.
- 32. Fixed failure of Secure Boot Append/Update Keys.
- 33. Fixed inability to upload all OOB files on the first BMC boot.
- 34. Corrected memory device number in SMBIOS type 16.
- 35. Corrected iSCSI Configuration page.
- 36. Set DIMM size to recalibrate when rank is disabled.
- 37. Updated non-VPD Intel MAC report routine for 64bit BAR.