

BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

| | |
|-------------------------|--|
| Product Name | H12SSFF-AN6 |
| Release Version | 2.3 |
| Release Date | 10/21/2021 |
| Build Date | 10/21/2021 |
| Previous Version | 2.1 |
| Update Category | Critical |
| Dependencies | N/A |
| Important Notes | BIOS_H12SSFF-1C19_20211021_2.3_STDsp.bin - BIOS image BIOS_H12SSFF-1C19_20211021_2.3_STDsp.zip - BIOS image and flash utility package Notice: <ol style="list-style-type: none">1. BIOS R2.0 and above supports 7002 and next generation processor.2. Flash Utility in package supports BIOS R1.x update to R2.x only, cannot roll back. |
| Enhancements | <ol style="list-style-type: none">1. Changed BIOS revision to 2.3.2. Added support in SUM to upload and delete HTTPS TLS certificate.3. Set the BIOS setting "Relaxed Ordering default" to <i>Enabled</i>.4. Updated AGESA MilanPI to 1.0.0.6.5. Updated A010 GN B0 microcode 0A00104C.6. Updated AGESA RomePI to 1.0.0.C.7. Exposed Setup item "Enhanced Preferred IO Mode".8. Fixed the BMC Redfish Host Interface named as ethX when CDN was disabled.9. Disabled Legacy/EFI iSCSI support. |

| | |
|--------------|--|
| | <p>10. Exposed the BIOS setting "BankGroupSwapAlt", "SEV-SNP Support", "Enhanced Preferred IO Mode" and "Root Complex 0x00~0xE0 LCLK Frequency".</p> <p>11. Changed the default of "Wait For "F1" If Error" to <i>Disabled</i>.</p> <p>12. Set all oprom control items to Legacy when boot mode set to Dual.</p> <p>13. Added Redfish/SUM Secure Boot feature and updated OOB for secure boot and reserve.</p> <p>14. Added "Force Next Boot" to UEFI shell support.</p> <p>15. Updated A011 GN B1 microcode 0A00111D.</p> |
| New features | N/A |
| Fixes | <p>1. Fixed Intel X550 dropped during an on-off aging.</p> <p>2. Fixed SUM cannot modify AMD CBS settings.</p> |

Release Notes from Previous Release(s)

2.1 (06/04/2021)

1. Changed BIOS revision to 2.1.
2. Updated AGESA RomePI to 1.0.0.B.
3. Set all OPROM control items to Legacy when boot mode set to Dual.
4. Added force next boot to UEFI Shell support.
5. Updated AGESA MilanPI to 1.0.0.2.
6. Updated A011 GN B1 microcode 0A00111D.
7. Fixed problem of an AIOM card (Intel X550) dropping during an on/off aging.

2.0a (04/22/2021)

1. Changed BIOS revision to 2.0a.
2. Fixed problem of AFU/clnevnlog causing ROT BIOS recovery.

2.0 (02/23/2021)

1. Changed BIOS revision to 2.0.
2. Added support for both AMD EPYC 7002 and next generation processors.
3. Updated A011 GN B1 microcode 0A001119.
4. Updated AGESA RomePI to 1.0.0.A.
5. Fixed problem of BIOS initialization showing IPV6 address when IPV6 is disabled in the IPMI GUI.
6. Enhanced SMBIOS Type39 System Power Supply information.

1.0b (2021/01/28)

1. Reaction to BMC 00.01.25, BMC remove the reset from a changing LAN data within the 30/20 command. BIOS remove the patch.

1.0a (2020/12/19)

1. Changed BIOS revision to 1.0a
2. Patched problem of POST randomly hanging at B2 during AC aging.
3. Corrected OEM FID VBIOS version.

1.0 (2020/12/14)

Initial release.