## **IPMI Release Notes**

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X12SPL-(LN4)F
Release Version	01.01.24
Build Date	07/01/2022
Previous Version	01.01.17
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	<ol> <li>Enable i2cmap protection feature.</li> <li>Improve BMC boot stability.</li> <li>i2cmap feature validated by Engineer.</li> </ol>
New features	N/A
	Fixed the following issues:
Fixes	<ol> <li>Power Average Usage reading value is higher then Max Peak value under Power Consumption.</li> </ol>
	2. VROC RAID status still shows ok even when RAID has been downgraded.
	3. Special query caused 500 Internal Server Error at X12 redfish (\$expand).
	4. Fixed judgment mechanism for network AOC health status.
	5. Inconsistent behavior between BMC and BIOS manual Recover.
	6. Maintenance event log display error at /cgi/op.cgi (config_smtp).
	7. Active Directory Remote Group character cap too short.