BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	H12DGO-6
Release Version	2.4
Release Date	08/11/2022
Build Date	08/11/2022
Previous Version	2.3a
Update Category	Recommended
Dependencies	IPMI firmware 1.01.09
Important Notes	 ECO #27109 BIOS image: BIOS_H12DGO6-1C1E_ 20220811_2.4_STDsp.bin BIOS Update package: BIOS_H12DGO6-1C1E_ 20220811_2.4_STDsp.zip Note: BIOS R2.x supports 7002 and 7003 processor. Flash Utility in package supports BIOS R1.x update to R2.x only, cannot roll back. R2.x BIOS default boot mode has been changed to EFI. If your OS is legacy, please press Del during POST to enter into the BIOS setting page to change boot mode after upgrade to R2.x. All GPUs showing GPU0 / System Slot 0 in IPMI GUI is a known issue, and will be fixed by next BIOS version.
Enhancements	 Updated Milan AGESA to 1.0.0.8. Updated Rome AGESA to 1.0.0.D. Changed BIOS revision to 2.4.
New features	N/A
Fixes	1. Fixed issue where NUMA NPS4 hangs system during POS in full load configuration.

Release Notes from Previous Release(s)

2.3a (06/21/2022)

- 1. Changed BIOS revision to 2.3a
- 2. Fixed issue of VRM checking failed.
- 3. Fixed issue of BMC static IP cannot be set.

2.3 (05/09/2022)

- 1. Changed BIOS revision to 2.3.
- 2. Updated Milan AGESA to 1.0.0.6 to support Milan-X processor.
- 3. Used BMC NIC MAC address to generate UUID.
- 4. Exposed EDC setup options in BIOS setup.
- 5. Changed PCIe AER setup default to disabled.
- 6. Remove some KCS command to patch hang 92 issue.
- 7. Add new AIOM support with NIC device VID 0x8086 DID 0x15ff.
- 8. Fixed issue of OS generated USB overcurrent warning.
- 9. Fixed issue of incorrectly display correctable memory error in SEL.
- 10. Fixed BMC missing problem during CBURN on/off testing.

2.1a (10/22/2021)

- 1. Changed BIOS revision to 2.1a.
- 2. Updated AGESA code.
- 3. Revised workaround for Nvidia-smi GPU lost issue.
- 4. Changed PCIE S0P2&S1P2 bifurcation to x16.
- 5. Changed PCI/PCIE Slot2 OPROM setup string from x16 to x8.
- 6. Added workaround on PCI/PCIE OPROM execution.
- 7. Fixed issue of build date is correct.
- 8. Fixed issue of BIOS hangs on POST code 92 with full system configuration.

2.1 (07/27/2021)

- 1. Changed BIOS revision to 2.1.
- 2. Updated AGESA code for 7002 processor.
- 3. Updated SMC modules.
- 4. Set UEFI shell boot order ahead of AIOM PXE.
- 5. Changed bifurcation of riser slot1 from 2x8 to 1x16.
- 6. Fixed failure of 4TB memory to boot.
- 7. Fixed missing Network Configuration in SUM BIOS configuration file.
- 8. Updated SMBIOS Type 2 board name to H12DGO-6.
- 9. Fixed failure to eject NVMe4 and 5 under Windows.
- 10. Fixed support for SMBIOS Type 9 AIOM card.
- 11. Fixed insufficient resources of some GPUs under Linux.

2.0c (06/03/2021)

- 1. Changed BIOS revision to 2.0c.
- 2. Modified UEFI shell boot order ahead of AIOM PXE with Milan CPU.
- 3. Fixed PCIE Gen drop issue on PLX switch downstream ports.

2.0b (05/24/2021)

- 1. Changed BIOS revision to 2.0b.
- 2. Added CPU and NB menus to SUM setup template.
- 3. Updated Rome/Milan AGESA code to 1.0.0.A/1.0.0.1.
- 4. Added delay in reading PSU FRU through BMC.
- 5. Changed system onboard slot number to 11.
- 6. Added a patch to solve NVidia-smi GPU loss issue with Intel NIC installed on switch board.
- 7. Added a workaround to assign 32bit resource for AIOM NICs to support legacy PXE.
- 8. Applied BIOS setup settings pushed by SUM without entering BIOS setup.
- 9. Changed PCIe port PMEM size.
- 10. Added support for unique filename.
- 11. Improved UOL data transfer between BIOS to BMC.
- 12. Corrected help strings in PCIe/PCI/PNP configuration page.

2.0a (03/25/2021)

- 1. Changed BIOS revision to 2.0a.
- 2. Removed unused SATA ports in BIOS setup.
- 3. Updated SMBIOS TYPE 9 and 40 table.
- 4. Treated AIOM as onboard NIC.

2.0 (03/04/2021)

- 1. Changed BIOS revision to 2.0.
- 2. Added support for both AMD EPYC 7002 and next generation processors.
- 3. Added support for Nvidia A100 80G GPU.
- 4. Improved SMBIOS Type 39 PSU reading procedure.
- 5. Added xGMI setup options.
- 6. Fixed problem of NVMe hot-swap resetting the system.
- 7. Fixed inability to enable ECC reporting by Cburn.

1.0a (12/10/2020)

- 1. Changed BIOS revision to 1.0a.
- 2. Provided all of AIOM NIC MAC addresses to BMC.
- 3. Fixed issue of CPU2 dropping.

1.0 (11/13/2020)

First release.