

BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X12DPG-U6
Release Version	01.01.37
Release Date	01/18/2023
Build Date	12/26/2022
Previous Version	01.00.21
Update Category	Critical
Dependencies	None
Important Notes	None
Enhancements	1."M2_SSD Temp" should be "M2SSD Temp", which follow Supermicro_BMC_Sensor_Naming_Guildeline_2.1.xlsx. 2.Improve bmc boot stability 3.Improve the stability of bios related ROT operations.
New features	1.Add option in BMC UI to create disabled user or edit user to disable. 2.Support Preserve BIOS Boot Options Configuration when updating BIOS FW. 3.Max number of SEL up to 4096. 4.i2cmap protection review
Fixes	1.[137924] STD -- 16416 -- 01.01.22 (2022/02/15) -- Add SNMP type user Not have * to inform Auth Key and Private Key are required items 2.[138264] ECO -- 16774 -- 01.01.16 (2022/02/15) -- Language Change title string not translated

	<p>4.[137300] ECO--15340-- 01.01.13(01/27/2022) -- Create new user on web UI should not get error, even though the user ID is occupied on NoAccess user.</p> <p>5.[138110] ECO--15340-- 01.01.16 (02/15/2022) -- It should not present "Delete" icon while login "Operator" or "User" privileges account. [138112] ECO--15340-- 01.01.16 (02/15/2022) -- Modify password while login "Operator" or "User" privileges account will return Oops error!</p> <p>6.[137093][Redfish API Automation test failed]</p> <p>7.[137368] [ECO -- 10349 -- 01.01.13 (20220127) -- Mount failed pop up error message and Even log are incorrectly</p> <p>8.[137442] ECO -- 15338 -- 01.01.13(20220127) -- Mount *.img display wrong file type on Java iKVM Virtual Media</p> <p>9.[137357] ECO -- 17274 -- 01.01.13(01/27/2022) -- Update invalid FW will show MEL message when update BIOS and CPLD</p> <p>10.[136988] IPMI ECO] Unspecified Event Log Assertion When AC ON</p> <p>11.[136663] ECO -- 17046 -- 08.10.19 (01/07/2022) -- iKVM(JAVA plug-in/HTML5) should be support IMA file type. [137280] ECO--15340-- 01.01.13(01/27/2022) -- iKVM(JAVA plug-in) should be support "IMA" image.</p> <p>12.[136607] IPMI ECO Update BIOS failed</p> <p>13.Storage feature broken in 01.01.10.</p> <p>14.STD -- 17212 -- 01.01.04 -- [Security] Specific strings could brute force the BMC directory.</p> <p>15.[135002] STD -- 17212 -- 09.14.10 BETA -- [Security] ipmitool can set lan mode out of range</p> <p>16.[134964] [BMC-Intel VROC 7.5 OOB] Please grey out "Create Raid" icon if no more physical drive available to create new Raid volume.</p> <p>17.[134545] STD-- 18379 -- 01.01.00-- Function -- Can't sync NTP server when BMC has IPv6 DNS</p> <p>18.[134183] STD -- 17212 -- 01.01.08 -- Password goes wrong when contains \</p> <p>19.[134282] STD -- 17212 -- 01.01.08 -- [Security] XSS attack at Notification Alert Redfish protocol</p> <p>20.[139329][DVT SYS-F511E2-RT] Judgment mechanism for network AOC health status</p> <p>21.[139811] STD --18605 --X12DGO -- 01.01.04 -- Inconsistent behavior between BMC and BIOS manually Recover</p> <p>22.[135651] STD -- 17212 ?V 09.14.10 BETA ?V [Security] Maintenance event log display error at /cgi/op.cgi (config_smtp)</p> <p>23.[140173] STD -- 17212 -- 01.01.16 -- [Security] Special query caused 500 Internal Server Error at X12 redfish (\$expand).</p> <p>24.[139748][X12DPG-U6][IPMI ECO 01.01.17] Redfish compare sensor info failed with smcipmitool.</p>
--	--

	<p>25.[142830] Standard -- 16914 -- 1.1.23 -- Active Directory Remote Group character cap too short</p> <p>26.[142091] ECO -- 16914 --01.01.17(2022/03/04) -- VROC RAID status still show ok When RAID is degrade.</p> <p>27.Avoid ME hang during bios-cloning-GOLDEN operation</p>
--	--

Release Notes from Previous Release(s)

01.00.21(10/22/2021)

- 1.Better compatibility with redfish ATT, after applying the security patches.
- 2.[129981] Creation and activation of a null user and password
- 3.[130474] BMC crash and forceful restart caused by malicious data transmission
- 4.Configurations in "resolv.conf" file cannot be reset after BMC is restored to the factory default setting
- 5.TEE OS 0x42 error message on IPMI MEL doesn't match with "Kernel code segment (offset: ##) was compromised
- 6.Remove Remove Chassis Intru SDR.
- 7.Fix SUM inband feature broken
- 8.[131124][X12DPG-U6]CPU node will loss BMC connection if cold reset CarrierBoard BMC in system without AIOM.
- 9.[130982] ECO -- 20033 -- 01.00.39 BETA (09/11/2021) -- NTP show fail message after setting
- 10.System with AST2600 have hang issue when running DC on/off testing with Red hat 8.3, We find the eSPI will hang after system hang, Aspeed provide us to clear 0x1e6ee080 bit 30 to 0.
- 11.[132314] WebGUI does not show the motherboard name in the dashboard after updating the BIOS and BMC
- 12.[X12DPG-U6]CPU node will loss BMC connection if Carrier Board RJ45 link down and change network segment.

01.00.18 (09/08/2021)

- 1.Shouldn't allow user to set user name and word to the same
- 2.config can't save Sendre of SMTP
- 3.webGUI "CPU Speed" info data source has been fixed from MaxSocketSupportedSpeed to OperatingSpeed
- 4.[webGUI] Hide LAN1 MAC Address if it is 00:00:00:00:00:00
- 5.Evidence should not blocked fwUP in 2021-07 release.
- 6.After MB cpd fwUP, if system is off, bmc will power_on the system.
- 7.Implement hyper link of carrier board IP address
- 8.[130496] Can't open JAVA iKVM under Windows Server OS
- 9.Refactor FD related codes
- 10.Remove VTT and VPP SDR first, because this HW design and SW design have limitations, it will trigger SEL when test system DC on/off stress.

01.00.12 (07/20/2021)

- 1.webGUI login should be ok after a session reset.
- 2.[128071] Onboard LAN MAC and information mismatched between on "Network AOC - Component info" and "Dashboard"

3.[127933] [AST2600 A3] system hang and lost BMC connection after update CPLD from WebGUI or SUM

4.[127840] Beta -- 16728 -- 01.00.07 -- RADIUS Server Address Input Issue Copy Project Issue Link

5.[New feature] Change location name in NIC page (AIOM->System Slot A#, PCIE-> System Slot #)
Fetch location name from [Chassis/1/Thermal]

When thermal name include [AIOM], the location field should show [System Slot A#].

When thermal name include [AOC], the location field should show [System Slot #].

When thermal name include [AOCUR_NIC] the location field should show [System Slot 0].

6.bmc boot firmware flash uses 3byte mode

7.Improved bios update internal flow

8.Better compatibility with provisioning rot_checker script 2021Q2.

9.When a new image being programmed is introducing a new/late version of RollbackID to the one programmed in RoT,

BMC will automatically update Golden Image in addition to Active Image because the Golden Image with smaller RollbackID to that in RoT is unusable for recovery.

10.bios firmware upgrade, refactored the codes.

11.[128572] T4 GPU temperature sensor show as NA on BMC (feature broken in bmc 01.00.11)

12.Help Page is not matched with CarrierBoard IPMI Web

Date