

IPMI Firmware Release Notes

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X11SPH-nCT(P)F
Release Version	1.74.13
Build Date	8/2/2023
Previous Version	1.74.11
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	None
New features	None
Fixes	<ol style="list-style-type: none">1. IPMI configuration backup file remote command execution.2. Security Fixes: CVE-2023-40287, CVE-2023-40288, CVE-2023-40286, and CVE-2023-33413.

1.74.11 (10/27/2022)

1. *Optimized the execution time on the VRM utility.*
2. *Blocked the I2C master write and read command for VRM channel (channel 1).*
3. *Virtual Media on the HTML5 iKVM console is nonfunctional.*
4. *VRM utilities can be used on X11QPH+ when the battery is INSTALLED.*
5. *Disconnecting problems when switching from 1G switch to 100M switch. (This is a workaround solution.)*

1.74.02 (2/25/2022)

1. *Added support for the new Realtek PHY RTL8211FD-VX-CG driver.*
2. *Added support for the Supermicro 39xx, 38xx storage card sensor reading.*

1.73.14 (11/20/2020)

1. *Added support for PLDM sensor reading on AOC NIC cards.*
2. *Enabled AOC_NIC_TEMP IPMI sensor during AC on/off test.*
3. *Implemented security fixes.*
4. *Removed ability to SSH using weak MAC algorithms.*
5. *Fixed multiple XSS on jQuery versions between 1.2 and 3.5.0.*
6. *Enabled saving domain name on AD page.*
7. *Enabled FW to show PSU sensor reading under web GUI.*
8. *Enabled deleting AD group from web.*
9. *Enabled SNMP alerts to show up in "Trap Receiver."*

1.73.06 (11/20/2020)

1. *Changed Storage WebUI.*
2. *Added support for device auto-discovery within a rack for RSD.*
3. *Added support for Redfish 1.8 API.*
4. *Added support for HTML5 VM, BMC UI, and Redfish system component health status, and changed remote console UI.*
5. *Added support for IPv4 and IPv6 stack selection.*
6. *Added support for BMC KCS interface security solution.*
7. *Added support for WebUI button requirements.*
8. *Added support for AOC NVMe M.2 sensor reading.*
9. *Added support for IPv6 and FQDN address configuration.*
10. *Added support for SNMPv3 Trap and new MIBs feature.*
11. *Corrected error message from 'User name must be 4~16 characters.' to 'User name must be 4~15 characters.'*
12. *Corrected typo in SSL Certification confirm window.*
13. *Fixed problem of user being permanently locked out after exceeding lockout times by SMCIPMITool.*
14. *Fixed failure of Redfish automated test.*
15. *Fixed failure to set LDAP Server Address through SMCIPMITool.*
16. *Fixed failure of SUM 2.5.0 (2020/04/17) to execute Get GpuInfo command function.*
17. *Fixed malfunction of fan control with AOCM2.*

18. Fixed failure of Linux OS to reboot due to BMC firmware.
19. Fixed failure of IPMI ECO Automation caused by KCS error.
20. Fixed problems of IPMI displaying the same location for two AOCs at different bus numbers, the "Model:" item reporting "UNKNOWN 0x00000000" in the controller information table, the "Manufacturer:" item displaying "Illegal Vendor ID" for the controller information, vendor information displaying incorrectly for HDD SATA drive at Physical Drive View, and Device 0 and Device 1 both displaying at slot 2.
21. Fixed failure of installed NVMe SSDs to display in latest IPMI firmware Rev. 1.73.01 (3/16).
22. Fixed failure of OOB BIOS update function via SUM 2.5.0.
23. Fixed missing event log for yellow icon in System Health.
24. Fixed problem of the Storage Monitoring page appearing without storage card present.
25. Fixed failure of IPMI ECO Robot test.
26. Corrected license for HTML5 VM.
27. Fixed inconsistency between X11 and X10 firmware for long hostname string.
28. Fixed failure of SUM test.
29. Fixed problem of SMASH only taking up to 403 characters before disconnecting.
30. Fixed missing IPMI sensor during AC on/off test.
31. Fixed hardware information.

Product Manager

Date