

IPMI Firmware / BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	H12SSW-NTR
Release Version	2.6a
Release Date	08/28/2023
Build Date	08/28/2023
Previous Version	2.5
Update Category	Recommended
Dependencies	N/A
Important Notes	ECO #28692 BIOS Image: BIOS_H12SSWR-1B74_20230828_2.6a_STDsp.bin - BIOS image BIOS Update Package: BIOS_H12SSWR-1B74_20230828_2.6a_STDsp.zip Please update BIOS with attached Flash Utility in package.
Enhancements	<ol style="list-style-type: none">1. Update Milan B0/B1/B2 stepping CPU microcode and Milan-X B2 stepping CPU microcode for AMD-SB-7005 Security Bulletin to address CVE-2023-20569 issue.2. Support the Supermicro System LockDown feature.3. Update Rome B0 stepping CPU microcode 0x0830107A for AMD-SB-7008 Security Bulletin to address CVE-2023-20593 issue.4. Add Rocky Linux Boot Option Name.5. Enable token ASM1061_Workaround to disable ASM1061 64-bit memory address capability.6. Update MilanPI to 1.0.0.A based on 5.22_MilanCrb_0ACOU021 for AMD-SB-1032.7. Update Milan B0/B1/B2 stepping CPU microcode and Milan-X B2 stepping CPU microcode to patch Patch for Errata 1304, 1310, 1311, 1313, 1329, 1330, 1336, 1343, 1350, 1352, 1361, 1378,1379, 1381, 1386, 1407, 1433, 1450.8. Follow the SMBIOS template sync the chassis type from FRU0 to SMBIOS Type 03, only for H12 projects.9. Update AGESA RomePI to 1.0.0.F based on 5.14_RomeCrb_0ACMK026 for AMD-SB-1032.10. Modified GetVariable() service for buffer overflow in certain cases.
New features	N/A
Fixes	<ol style="list-style-type: none">1. Fixes keep the PCIe original bifurcation when the required link width for the AOC-SLG card is greater than x4.2. Fixes When AsMedia SATA Controller Disabled SUT will hang at post code "92"

Release Notes from Previous Release(s)

Revision 2.5(2022/10/06)

1. Update Milan AGESA to 1.0.0.9
2. Update Rome AGESA to 1.0.0.E
3. Follow the SMBIOS template and sync the chassis type from FRU0 to SMBIOS Type 03.
4. Fixed the system can't boot to UEFI USB KEY with command 'ipmi power bootoption 11'.
5. Fixed Update SMBIOS type 41 data. Change "NEC USB" string to "Renesas USB"

Revision 2.4(2022/02/23)

1. Update Milan AGESA to 1.0.0.8
2. Update Rome AGESA to 1.0.0.D
3. Fixed the system randomly hanged postcode "0x00"/"0xCd"/"0x4b" when the system runs AC On/Off burning test.
4. Fixed the system hanged postcode "AC" when TPM 2.0 module is installed.
5. Fixed the MAC address of AOC-A25G-i2SM that can't show in BMC Web UI.
6. Fixed Milan and Milan-X CPU can't detect AMD GPU MI210 populated on slot-1 but Rome can.
7. Change each root bridge MMIO size from 16M to 64M to fix out of resource issue.

Revision 2.3 (2021/10/01)

1. Update Milan AGESA to 1.0.0.6
2. Update Rome AGESA to 1.0.0.C

Revision 2.2 (2021/08/09)

1. Followed the new cable plan to change the G1 & G2 PCIe config.
2. New AIOM card (AOC-A100G-m2CM) is Support; BIOS supports this AIOM card for BMC sensor reading.
3. When the AIOM1 changed device, the BMC gets a reset. However, it causes the BIOS cannot update the OOB file successfully.
4. Update BIOS version from 2.1 to 2.2
5. USB controller PCIe gen. speed fix from PCIe Gen. 1 to PCIe Gen. 2

Revision 2.1 (2021/07/12)

fixes the BIOS version shows incorrectly

Revision 2.0 (2021/05/25)

First release.