

BMC Firmware Release Notes

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X13DDW-A
Release Version	1.01.06
Build Date	10/20/2023
Previous Version	1.00.58
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	<ol style="list-style-type: none">1. After WebGUI MB_CPLD1 FWUP, the system should be auto-power-on.2. Host Interface page can be configured in system lockdown mode or login with User privilege.3. HTML5 Console as default.4. Dual mode for network setting as default.5. Virtual media support 3 CD/FLOPPY image mounting.
New features	<ol style="list-style-type: none">1. Supported RMCP+ Cipher Suite 15/16/17.2. Keyword in the search bar will be clear after disabling thresholds. Keyword in the search bar will be clear after turning "OFF" thresholds.3. Added new user tips exceeds the frame when zooming to 110% (Browser: Edge).4. Health status of the task list is not complete when zoomed in from 75% to 200%.5. Uploaded invalid IPMI Configuration file help tips overlap when zoomed in to 200%.6. Power consumption is not complete when zoomed in from 110%.7. Sensor threshold columns should not hide when exported to Excel file. Sensor thresholds are not complete/overlap/disappear when zoomed from 100%.8. Disabled IPMI Lan Port Interface.

Fixes	<ol style="list-style-type: none"> 1. Fixed RA provisioning. 2. WEB – Syslog license dialog message doesn't match with spec content. 3. Set IPV6 and deleted IPV6 through SMCIPMITOOL failed follows issue. 4. WEB – Unable to delete LDAP and AD server address Copy Project Issue Link. 5. WEB – MEL is incorrect after doing iKVM reset. 6. Remote Console Preview current interface button enabled. 7. Can't generate evidence after recovery BMC/BIOS. 8. After Redfish request on NTP and refresh Task List becomes empty. 9. Active Directory failed to delete the server address. 10. Source of MEL "Smash logout was successful" shouldn't be shown as N/A. 11. [SYS-211GT-HNTF][HDS-SMP-MZWLO1T9HCJRB5C] Disk Info/Product Name/Firmware Revision displayed incorrectly under BMC WebUI. 12. Redfish have health sensor failed. 13. NVMe info should be the same after UpdateBMC Fail. [AS-1115SV-WTNRT_EVT_H1] The NVMe info is incorrect. 14. SNMP OID 'UID' always gets 0 whatever UID is switched to ON or OFF. 15. Fixed SSM Diagnose System fail due to PATCH Redfish bios API return 500 internal error. 16. Hint message misplacement. 17. Failed to delete the search base in the LDAP Configuration. Search base display ISNULL after the data has been removed. 18. "Verify SSL Certificate" and " Accept Self-signed Certificate" shouldn't be selected if setting File Server to http://xxxxx. 19. No Temperature Sensor for 100G Omni-path AOC.
-------	---