IPMI Firmware Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	H13SSF	
Release Version	01.02.04	
Build Date	12/01/2023	
Previous Version	01.01.07	
Update Category	Enhancement	
Dependencies	BIOS: v1.6 (BIOS_H13SSF-1D16_20231031_1.6_STDsp)	
Important Notes	IPMI image: BMC_H13AST2600-ROT20-E401MS_20231201_01.02.04_STDsp.bin IPMI Update package: BMC_H13AST2600-ROT20-E401MS_20231201_01.02.04_STDsp.zip	
Enhancements	N/A	
New features	 1.Added support for KCS disable function. 2.Added support for LDAP StartTLS. 3.Added SPS version and Microcode version to firmware inventory. 4.Switched "validate Access with OOB and No License" to newer UI behavior. 5.Enabled USB Lan 2 options feature (WEB). 6.Added support for OpenJDK.7.Added Property "Product" for /redfish/v1. 	
Fixes	1.Fixed an issue where the default value of the DNS Server Address did not match the definition of each field 2.Fix an issue where only partial memory modules were listed in the IPMI Web GUI memory info with HBM CPU. 3.Fiexed an issue that valid TSIG files could not be uploaded. 4.Fixed an issue that syslog packet does not follow RFC3164. 5.Fixed some failure issues in redfish automated test items. 6.[MEL]Fixed incorrect MEL when disabling the Host Interface 7.Fixed Virtual media display "This function requires SFT-OOB-LIC license!" tip when both DCMS and OOB keys have been activated.	

- 8. Fixed an issue that the IP Access Control page can be edited/deleted based on user privileges.
- 9. Fixed an issue that the IPMI Web GUI main menu ordered incorrectly in Safari.
- 10. Fixed an issue that SPPT detects DIMMA F &DIMMG L Temperature -16 $^\circ$ C.
- 11. Fixed an issue that the BMC GUI "System Health" status ' did not change to a critical condition when a system fan failed.
- 12. Fixed DMTF validator failure.
- 13. Fixed an issue that VLAN Tagging tests failed.
- 14.[OSS]Fixed abnormal Login UI display after performing Factory Default
- 15.[Virtual Media]Fixed an issue that the Checkbox and Conncect icon styles do not follow the specification.
- 16. Fixed an issue where error messages would not appear when uploading XML files during BIOS update.
- 17.[MEL]Fixed adding dhcp dns needs to generate MEL.
- 18. Fixed an issue that prevented downloading of BIOS/BMC Evidence without a license.
- 19.[Virtual Media]VM is able to add duplicates, three items with the same Share Host, and Path to Image.
- 20. Fixed an issue that LLDP pages were not translated into the selected language.
- 21.[Virtual media]Fixed VM showing "This function requires SFT-OOB-LIC license!" tip when both DCMS and OOB keys are enabled.
- 22. Fixed being unable to disable Dynamic DNS if TSIG is enabled, TSIG must be disabled first.
- 23. Fixed an issue that IPv6 link local addresses could not be displayed.
- 24. Fixed BMC not being able to detect temperature reading AOC-E810-XXVDA4TGG1.
- 25. Fixed an issue with no U.2 NVMe temperature when installing INTEL SSDPE2MD800G4.
- 26. Fixed an issue that the connect button did not work on the Virtual Media page.
- 27. Fixed some failed items of IPMI ECO redfish automation test.
- 28.[GUI]Fixed the problem of misalignment of the Dashboard page layout.
- 29.[GUI]Fixed an issue that the link speed description in the Help info was inconsistent with the Spec.
- 30. Fixed the license Activate page not changing wordings from "New Private Key" to "New Product Key".
- 31.[SMCIPMITOOL] Fixed an issue with inconsistent return code behavior when executing "ipmi lan ipv6 clear".32.[GUI] Fixed the problem that the Checkbox style of the ADD USER page does not follow the specification.
- 33. Fixed RMCP connection loss issue during SPM testing.

- 34. Fixed an issue of overlapping warning messages when adding a new user.
- 35. Fixed an issue that IPMI showed the system's power consumption was way too low.
- 36. Fixed an issue that the IPMI manufacturer name as "unknown".
- 37.[Virtual Media]Fixed the Unmount Device modal buttons showing Close and Save instead of Yes and No even though it asks "Are you sure you want to UNMOUNT the Device?"
- 38. Fixed Error message displayed when mounting image.
- 39. Fixed an issue that virtual media could not be connected when only one or two virtual machines were set up to connect.
- 40.[MEL]Fixed an issue of incorrect MEL when modifying IPV4 DNS Server2 IP.
- 41. Fixed an issue that the Virtual Media/Network/User(SNMP) in the Help page is inconsistent with the Actual WEB page.
- 42. Fixed abnormal behavior after clicking the Save button multiple times to delete a task.
- 43. Fixed an issue that "User is locked" would not pop up due to [Security] considerations.
- 44. Fixed missing physical View HDD temp issue in BMC.
- 45.[MEL]Fixed an issue when deleting DNS Server and Server2 IP and saving doesn't generate MEL.
- 46. Fixed an issue that valid IPv4 address for static Ips could not be saved.
- 47.Fixed an issue that unconfigured SSDP-related MEL would be triggered when setup SSDP.
- 48. Fixed some failures in BMC Web UI automated testing.
- 49.[MEL]Fixed an issue when enabling Auto Daylight Saving failed but MEL shows enabling successfully.
- 50. Fixed an issue that the title of the Virtual Media page doesn't follow the UI design.51. Fix an issue that the help page did not list SSDP & LLDP related information.52. Fixed an issue that warning tips would continue to be displayed after unselecting the Account Type 'SNMP' when adding users.
- 53. Fixed an issue when the PSU sensor was missing when executing an AC cycle.
- 54. Fixed Systems LogService entry empty data.
- 55.Added ACCEPT/DROP rules with duplicate IP Address/Mask being blocked.
- 56.[GUI]Fixed an issue that the password could not be reversed with the User name and the error response "Oops! Something went wrong." was inconsistentwith the situation.
- 57. Fixed an issue that the trash can should appear gray when logging in with User privilege.
- 58.[MEL]Added RemoteGroup/User Rules MEL did not follow the same MEL SPEC version definition.

- 59.[MEL]Duplicated MEL does not match the option name when setting Dedicated Link Speed & 1G Full Duplex MEL.
- 60.[MEL]Fixed an issue that SNMPv3(Notifications) Authentication Protocol/Encryption Protocol naming is inconsistent with MEL.
- 61. Fixed an issue that SSDP IPv6 Scope settings could not be saved. (either logged by MEL)
- 62. Fixed wrong license required behavior/message.
- 63.Fixed wrong Redfish privilege and licensecheck for
- Redfish_1_11_API_full_list_20230918 update.
- 64.Set 0.0.0.0 to DNS Server IP would be replaced by a valid DNS Server2 IP after the setting is saved.
- 65. Fixed incorrect GPU Index from IPMI.
- 66.Fixed HDD Temp/HDD Temp sensor will show N/A when executing cburn-87 DC on-off test.
- 67.Changed the upper critical temperature to 77 $^{\circ}\,$ C for the E3.S SSD drive sensor.
- 68. Changed the upper critical temperature to $80^{\circ}\,$ C for Samsung NVMe drives.
- 69. The setting is in the correct format, but the NTP server IP is invalid. The error message shows "Oops" instead of [MEL-0255].
- 70.[GUI] Fixed a virtual Media/Network/User(SNMP) inconsistency between the Help page and Actual WEB page.
- 71. Duplicated MEL does not match the option name when setting Dedicated Link Speed & 1G Full Duplex MEL.
- 72. Fixed the wrong "RAID level" information on the BMC Web GUI when creating RAID level 10/50/60(Span Depth=3).
- 73. Fixed [MEL-0104] non-listing issue that all configurations were not preserved after successfully updating the BMC.
- 74. Fixed the failure of SPPT validation.
- 75. Fixed incorrect MEL when configuring Host Interface.
- 76. Fixed an issue with no related MEL when TSIG Authentication is disabled.
- 77. Fixed the issue that NVMe temperature would sometimes reach to $45^{\circ}\,$ C.
- 78. Fixed an issue with empty uffn in backup or golden inventory.
- 79. Fixed the issue of "null users are not displayed on users page".
- 80. Fixed the issue of "Failed to Set LAN AutoConfiguration DHCPv6Mode Configuration".
- 81. Fixed the inconsistency of notifications (SNMP) between the Help page and actual web page.
- 82.[MEL-0093] Fixed the issue of "string not match with LAN Interface option naming".
- 83.[Redfish]Fixed
- '/redfish/v1/Chassis/StorageBackplane/Drives/Disk.Bay.0' wrong status code.
- 84.[SMCIPMITOOL][IPV6]Fixed the issue of "Fail to set Alternative DNS

server IP through SMCIPMITOOL".

85.[SMCIPMITOOL]Fixed an issue of BMC being temporarily disconnected when setting ipv6 dns 2 via command.

86.[SMCIPMITOOL]Fixed the issue of "DNSv4 mode raw commands doesn't work".

87.[SMCIPMITOOL] Fixed an issue of the wrong command return code.

88. Fixed the issue of "no Fan 6 sensor reading".

89. Fixed Redfish Inconsistency.

90.Fixed SUM -- Failed to Set LAN AutoConfiguration DHCPv6Mode Configuration.

91. Fixed the issue that users were unable to load SMTP pages.

92. Fixed the issue that redfish test failed on Check Account Service Accounts Method Privileges due to unexpected status code returns.

93. Fixed the issue that there is an extra backplane object on the BMC "Firmware Management" page.

94. Fixed the issue that the operator cannot have Full Access to the Event Log.

95. Fixed the issue that PATH

'/redfish/v1/Chassis/StorageBackplane/Drives/Disk.Bay.0' status code should be 405 but is actually 400.

96.[MEL] Fixed an issue with incorrect MEL when restoring to factory defaults. (raw 30 41)

97. Fixed the issue that logging out with enabled SMTP alert will create three MEL entries.

98. Fixed the issue that RoT State changed to disabled after factory reset

99. Fixed the issue that the BMC Host Interface becomes "Disabled" 100. Added MEL after changing the Host Interface "RNDIS Connection" or "CDC-ECM Connection".

101. Fixed the issue that Nvidia L40 GPU has no sensor and information.

102. Fixed the issue that the string did not match LAN mode naming.

103. Fixed the issue that Notifications (SNMP) in the Help page are inconsistent with the Actual WEB page.

Release Notes from Previous Release(s)	
1.01.07 (7/10/2023)	
Initial release.	