

BMC Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X13DSF-A
Release Version	01.03.14
Release Date	07/18/2024
Previous Version	01.02.33
Update Category	Enhancement
Dependencies	None
Important Notes	None
Enhancements	1. Liquid Leakage UI implement 2. Remove Action of ResetToDefault parameter "PreserveNetwork" 3. Avoid wrong string and etag format in Redfish and Correct Redfish API deprecate and create. 4. Make Preserve Network backward compatible as redfish 2020 5. The System button of Dashboard no reaction 6. Update slot format of Physical Storage view 7. Redfish Upgrade 2021.2, RF1.14 8. Adjust license of OemDumpService. 9. Event service and redfish event Https allow self-signed CA. 10. Support new feature Each Field v1.33 11. OSS Requirements 12. Prompt text update - IKVM over maximum sessions 13. Added RSA2048 key for license server from new IT HSM 14. Update the SSDP Redfish version and fix possible exception 15. WEBUI HDD Temp and SSD Temp show null and correct Drive Status
New features	1. Add Smart NIC related schema and adjust smartnic url index 2. Support GPU-NVDPU-BA3220-C transceiver temp on BMC Web. 3. Support AMD MA350
Fixes	1. Improved BMC efficiency, compatibility and reliability.

Release Notes from Previous Release(s)

01.00.16 (10/28/2022) <i>Initial release.</i>
01.00.25 (01/04/2023) 1. Upgrade X13 crash dump version to 2.0.2 2. Support Xilinx U250 GPU, GPU NVIDIA L4 PCIe Card, AOC-S25G6-m2SM, Kioxia_CD6, AOC-SLG4-2H8M2, AOC-S3808L-L8IR, AOC-S3816L-L16IR, Intel PVC GPU, RTX A2000-6G, GPU NVIDIA RTX T1000 4G and GPU NVIDIA RTX T1000 8G. 3. Redfish method to set BMC LAN interface. 4. Improved BMC efficiency, compatibility and reliability.
01.01.10 (08/09/2023)

1. KVM launched and closed MEL should display user ID
2. Support Temp sensor reading of RTX 3090 GPU card.
3. Retrieve BIOS version from 'OFID'
4. Redfish 2020.3 related feature
5. BPN-E1S5-126ES2N CPLD firmware updating.
6. Support Motherboard CPLD Golden Image Version Display
7. Support Motherboard CPLD Golden Image Update
8. Task Queue & Task List in storage monitoring
9. Auto Daylight Saving Time.
10. support HBM sensor reading for NVIDIA GPU H100
11. Upgrade the Ethernet Interface version from v1.6.2 to v1.6.3 to align spec.
12. Dark Theme update.
13. Improved BMC efficiency, compatibility and reliability.

01.01.23 (10/24/2023)

1. [ENGINEERING] - empty ufn in backup or golden inventory
2. Improved BMC efficiency, compatibility, and reliability.
3. [ENGINEERING] - Support Nvidia GPU A30X.

01.02.33 (04/26/2024)

1. Web UI Prompts
2. support AOC-E810-XXVDA4, AOC-S400G-B1C
3. Upgrade SEL to 1.38 and merge sel search method to one function.
4. Upgrade MEL to 1.07 and Add MEL 70&368.
5. Redfish support BMC each field v1.33/ v1.34
6. DNS Server 1 & 2 IP ability to be set to duplicate values via SMCIPMITool
7. Web Function -- 0.0.0.0 is not allowed to be saved in 'Server Address'.
8. Server Address field can fill in over 255 characters which is not match with the Spec defined.(AD and LDAP)
9. Allow class D, E of IPv4 addresses for DNS Server IP setting.
10. Set invalid IPv6 Static Address raw command not return CC.
11. Updating the Backplane, Midplane, Fan/CPU/AIOM/AOM board CPLD all should now present MEL ID with the MEL
12. "BMC Reset " help info page description is inconsistent with UI Spec and BMC web
13. Improved BMC efficiency, compatibility and reliability.

01.03.14 (07/18/2024)

1. Liquid Leakage UI implement
2. Remove Action of ResetToDefault parameter "PreserveNetwork"
3. Avoid wrong string and etag format in Redfish and Correct Redfish API deprecate and create.
4. Make Preserve Network backward compatible as redfish 2020
5. The System button of Dashboard no reaction
6. Update slot format of Physical Storage view
7. Redfish Upgrade 2021.2, RF1.14
8. Adjust license of OemDumpService.
9. Event service and redfish event Https allow self-signed CA.
10. Support new feature Each Field v1.33
11. OSS Requirements
12. Prompt text update - IKVM over maximum sessions
13. Added RSA2048 key for license server from new IT HSM
14. Update the SSDP Redfish version and fix possible exception
15. WEBUI HDD Temp and SSD Temp show null and correct Drive Status
16. Add Smart NIC related schema and adjust smartnic url index
17. Support GPU-NVDP-BA3220-C transceiver temp on BMC Web.
18. Support AMD MA350
19. Improved BMC efficiency, compatibility and reliability.