

BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X14DBT-B
Release Version	1.0a
Release Date	07/09/2024
Previous Version	1.0
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	<ol style="list-style-type: none">1. Updated code base to 5.35_0ACQZ_3218D03_SRFAP_55_BETA for WW25 BKC.2. Updated Intel Giga LAN uEFI driver to BootUtil 29.1.3. Updated AST2600 VGA uEFI driver to 1.13.04.4. Changed PCI_DO_NOT_RESET_VC_MAPPING to enable.5. [SmcVPD] Patch for Mellanox InfiniBand Controller MAC Address issue.6. Filled DUID with UUID to avoid making all systems' DUID in IPv6 DHCP the same.7. Assigned unique display name for "Security Function" and "Password" published by SMC secure erase module.
New features	None
Fixes	<ol style="list-style-type: none">1. Changed callback protocol from gEfiRestProtocolGuid to SmcMmbiHostInterfaceAccessGuid since RNDIS may not be ready during POST.

- | | |
|--|--|
| | <ol style="list-style-type: none">2. [SmcEarlyConsoleStatus] Modified and updated SmcEarlyConsoleStatus to show EarlyVideo and Status messages in SOL and console during POST.3. Fixed duplicate ACPI objects.4. Fixed the VideoSelect abnormal problem.5. Fixed how the SAA reported garbage in the string SMC_STR_BOOT_DESCRIPTION_HELP.6. Patch M.2 device could not be detected after BKC WW23.7. Fixed the ITOS memory error check failure issue.8. Corrected the memory address of the ErrorRecord.9. Overwrote AmiPcdChassisType to sync SYS_CHASSIS_TYPE_1 setting. |
|--|--|