

BMC IPMI Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X13DAI-T
Release Version	1.03.14
Release Date	03/10/2025
Build Date	03/10/2025
Previous Version	1.02.06
Update Category	Critical
Dependencies	None
Important Notes	None
Enhancements	<ol style="list-style-type: none">1. HTTP server support for Feature flags via Redfish2. KCS Enhancement - Disable KCS via Redfish3. DMTF Compliance - Target URI of UpdateService4. Non-OEM messages of task monitor of simple update with code 202 response payload
New features	<ol style="list-style-type: none">1. Upgrade Redfish to 1.142. Redfish API support for Broadcom Expander3. On Board NVMe inject, eject4. Certificate support for HTTPS BOOT in Redfish5. JNLP & SOL retirement
Fixes	<ol style="list-style-type: none">1. "Reset Intrusion" function is not working normally.2. Date and Time cannot set correctly via PATCH method.3. Dashboard fail to display Host IPv6 address after add 6 address by ipmi raw command (30 68 09 01)4. MemoryMetrics at Redfish URI redfish/v1/Systems/1/Memory/num has OperatingSpeedMhz instead of OperatingSpeedMHz5. Log entries from OEM sensors at Redfish URI redfish/v1/Systems/1/LogServices/Log1/Entries/num do not have a SensorType property even though OemSensorType is present6. AOC-STGF-i2S should not show the link status under BMC UI7. AOC-AG-i2M should not show the link status under BMC UI8. IPMI Rom/FW update on AOC-S4116L-H16IR is successful but task list show failed with exception.

	<p>9. Out-of-bounds read/write at X13 and X12 IPMI (sdrs_checksum, Sensor_Init_Agent)</p> <p>10. IP Access Control Help page is inconsistent with UI spec. on WebGUI</p> <p>11. BMC Web UI cannot show the current memory operating speed Copy Project Issue Link</p>
--	---

Release Notes from Previous Release(s)

01.02.06 (04/22/2024)

1. Support Multinode URI
2. Auto daylight saving function
3. Web -- Default Iani value is Failover while MBD doesn't support Dedicated
4. Fix CVE-2023-4879 Terrapin Attack.
5. (CVE-2023-48795) SMC-2024010013 Terrapin Attack vulnerability, SMC-2024010010 Command Injection attack, SMC-2024010011 XSS attack
6. (CVE-2023-33413) SMC-2024010012 Command Injection attack

01.01.13 (01/20/2024)

1. Trapped in an endless loop of backup CPLD Golden
2. In WebGUI, bmc0->bmc2, bios0->bios2, bmc2->bmc0, bios2->bios0 features are broken since 01.01.09.

01.00.54 (05/23/2023)

1. UI Dashboard BIOS Firmware Version shows as 1.4b when it should be 1.5
2. SUM tool couldn't get BIOS build date, but web and SMCIPMITool show normally
3. Sensor reading not match with SPEC.

01.00.42 (01/23/2023)

1. First Release