

IPMI Firmware / BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	H11DSi/H11DSi-NT
Release Version	1.1a
Release Date	5/02/2018
Previous Version	1.1
Update Category	Critical
Dependencies	N/A
Important Notes	ECO #20833 BIOS Image H11DSI8.502 Please update BIOS with attached Flash Utility in package.
Enhancements	1. Updated AGESA NaplesPI to 1.0.0.7 based on AMI CRB_017.
New features	N/A
Fixes	N/A

Release Notes from Previous Release(s) – these will be appended at the bottom of the current release notes in italic and in smaller print

1.1 (04/13/2018)

- 1. Updated AGESA NaplesPI to 1.0.0.6 based on AMI CRB_015.*
- 2. Added support for graphic in Early Video mode.*
- 3. Added support for a hidden item "Memory Corrected Error Enabling" to disable OS logs CECC error*
- 4. Fixed inability to execute the iSCSI OPROM of onboard x550.*
- 5. Fixed problem of system hanging when Intel i350 LAN card is installed on SLOT3 or NVIDIA M10 on SLOT2.*
- 6. Updated AMI PSPDATA region and FV_BB in recovery mode.*
- 7. Fixed problem of UEFI LAN driver executing when CSM is disabled and onboard LAN Option ROM Type is Legacy.*
- 8. Fixed the location of SMCI signature in CMOS.*

- 9. *Fixed problem of SMBIOS types 1 and 2 not being kept after flashing BIOS.*
- 10. *Fixed inability to keep DMI data and some BIOS settings after SUM updates BIOS.*

1.0c (02/07/2018)

- 1. Updated AGESA code to NaplesPI 1.0.0.5 based on AMI CRB_014.
- 2. Fixed problem of only a single M.2 device being detachable from an AOC-SLG3-2M2 card when installed in slot #3.
- 3. Fixed inability to enter LSI3108 OROM by pressing keyboard via USB2.0 ports.

1.0b (12/28/2017)

- 4. Updated AGESA code to NaplesPI 1.0.0.3.
- 5. Implemented Machine Check Error (-22) workaround.
- 6. Added PCIe slot bifurcation support for AOCs.
- 7. Fixed problem of system stopping at post code 0x91.
- 8. Fixed problem of USB keyboards not responding when connected via USB 2.0 hub(s).
- 9. Fixed Memory Interleaving (Disable) functionality.
- 10. Fixed problem of OS IP being altered after flashing BIOS.
- 11. Fixed problem of Intel X550/X710 NIC link width dropping.

1.0a (10/31/2017)

- 1. Updated AGESA to NaplesPI_1.0.0.1 Patch 1.
- 2. Updated xGMI signal tuning tables.
- 3. Implemented display of ECC DRAM Error Location in BIOS and recording of log number in BMC SEL.
- 4. Removed “System Firmware Error (POST ERROR)” logging to BMC.
- 5. Removed “EFI 01030006” BIOS Event Log.
- 6. Fixed problem of SATA HDD location on Boot Menu indication not matching silkscreen.

1.0 (8/25/2017)

Initial Release