

IPMI Firmware

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X10DRU-I+
Release Version	3.75
Release Date	6/12/2018
Previous Version	3.66
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	1. Revised Redfish "Actions" for clearing event log.
New features	1. Added new Redfish features for downloading and uploading IPMI configuration. 2. Added adaptive temperature threshold in SDR for drives connected to 3108. 3. Enabled AC Power On Event log. 4. Added enable and disable options for 3108's JBOD mode over BMC's Web page and Redfish API "/redfish/v1/Systems/1/Storage/HA-RAID". 5. Added Redfish memory information feature. 6. Added support for saving 3108 storage controller status event. 7. Enabled monitoring of Broadcom 3108 BBU status and logging of it as status change.

<p>Fixes</p>	<ol style="list-style-type: none"> 1. Fixed grammar error on Event Log page. 2. Fixed problem of duplicate AOC NIC sensor appearing on sensor reading WebGUI. 3. Fixed failure of SEL to show bad disks at the very beginning. 4. Fixed inability of IPMI to detect removal or insertion HDD activity intermittently. 5. Fixed inability to view de-assertion messages after removed disks are put back. 6. Set AC Power On Event log to be reported when BMC executes cold reboot. 7. Enabled update of 3108's firmware over BMC's Web page. 8. Fixed problem of BMC not logging events when user removes pre-installed HDDs (connected to storage backplane and 3108) during system boot and after Broadcom 3108 storage controller is initialized. 9. Fixed problem of the sensor reading of AOC-STG-i4S card working abnormally. 10. Fixed problem of Redfish 500 being returned when NetworkProtocol is patched after factory default. 11. Fixed problem of the help page of iKVM/HTML5 console not supporting multi-language content. 12. Fixed inability to update 3108's firmware over BMC's Web page if Logical device is on the card. 13. Fixed timeout of Invalid Default Active Directory. 14. Fixed failure of the button to switch to upload in floppy disk after unmounting a file. 15. Fixed failure to change JBOD mode. 16. Fixed problem of "undefined" message appearing in pop-up window before uploading Broadcom 3108's ROM.
---------------------	---

Release Notes from Previous Release(s) – these will be appended at the bottom of the current release notes in italic and in smaller print

3.66 (1/30/2018)

- 1. Improved multi-language content on the iKVM/HTML5 option menu and submenu.*
- 2. Disabled MCTP support on Broadcom 3108 firmware so it only supports I2C protocol.*
- 3. Added support for Redfish firmware inventory (BIOS/BMC update).*
- 4. Added support for GPU V100.*
- 5. Fixed failure of SUM "Test_case_215 Outband - ChangeBmcCfg and compare".*
- 6. Fixed inability to disable LDAP Authentication immediately after enabling it.*
- 7. Fixed problem of product serial number being incorrect when it is longer than 15 characters and written in IPMI FRU.*
- 8. Fixed failure of SUM 2.0.1 Test.*
- 9. Changed the title of Trouble Shooting page to Troubleshooting.*
- 10. Fixed IPMI update message.*
- 11. Fixed syntax of CD-ROM image page's pop-up window.*