IPMI Firmware

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	B10DRi/C(-N)
Release Version	3.50
Release Date	6/1/2018
Previous Version	2.56
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	1. Set raw 0x30, 0x70, and 0xf2 to only clear OOB key and not DCMS key.
	2. Allow special characters for username and password.
	3. Enabled SDR to refresh when BMC reboots.
	4. Set syslog port to be read-only in Configuration->Port.
	5. Removed LSI3108 MCTP.
	6. Updated NTP version to 4.2.8p10.
	1. Added more power control records and BMC settings in Maintenance System
	Event Log.
	2. Added Refresh to HTML5 menu.
	3. Put syslog configuration under OOB license.
	4. Enabled system event log to record most configuring operation without requiring
	license key.
New features	5. Added save button to sensor reading WebUI page.
	6. Added "Activate License" to Miscellaneous page.
	7. Added support for new Intel NVMe P4500 1TB.
	8. Added support for NVMe P4500 fix for the problem of too many group lists being
	generated if "locate" or "stop locate" is clicked.
	9. Added support for GetSetBMCStatus command for TAS.
	10. Added ability to clear HTTPD and RAKP configuration to factory default page.

Fixes	1. NTP mode can get DateTime.
	2. Corrected Maintenance System Event Log DateTime.
	3. Power/temperature history record chart no longer shows zero.
	4. Set/get IP control commands now function in SMCIPMITool.
	5. Corrected an issue with iKVM user list.
	6. Corrected OOB command version.
	7. Allow erasing host name on network page.
	8. IPMI power/temperature record now plots correctly.
	9. Sensor readings now correct when sensor reading task generates too many
	events.
	10. Corrected Chinese language content on Configuration Alert page.
	11. CPU overheat no longer prevent sensor readings disabled/unable to display.
	12. Corrected virtual media function.
	13. Corrected IPMICFG failure to change BMC MAC address.
	14. Corrected KVM's inability to mount ISO.
	15. Removed FanMode from Blade BMC Redfish API because Blade FanMode is
	controlled by CMM.
	16. Show status of Miscellaneous->Active License.