

IPMI Firmware

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X11DPT-L
Release Version	3.67
Release Date	3/21/2019
Previous Version	N/A
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	1. Hardened Redfish webserver to prevent 500 error codes.
New features	1. Added support for hostname in Syslog configuration, IPV4, and IPV6. 2. Added support for LSI 3008/3216/3616 IT management without support for firmware update and logic volume management. 3. Added SPS FW downgrade enhancement & CLX CPU ID Check. 4. Added support for AD/LDAP/RADIUS hostname.
Fixes	1. Fixed inability to set user privilege to “no access” via CMD. 2. BMC no longer resets when deleting non-existing active directory group with SMCIPMITool. 3. Allow sorting health event log by date and time.

	<p>4. Stop showing all event severities as "Information" when sending test alert.</p> <p>5. BMC now reports correct Inlet Temperature to node manager.</p> <p>6. Fan no longer operates at full speed after changing mode from FullSpeed to Standard.</p> <p>7. Allow reading SMC power supply FRU.</p> <p>8. Fixed abnormal system power consumption under limited power policy.</p> <p>9. Patched CVE-2019-6260 pantsdown.</p> <p>10. Improved IPMI Get Device ID responses.</p> <p>11. Corrected BMC remote KVM and remote power control failures when multiple invalid logins occur in SMASH.</p> <p>12. IPMITool no longer hangs due to special characters &~`!@#\$%^*()_-=+{[] \:;'"<,>./ in username and password.</p> <p>13. Improved webUI displays after AD configuration.</p> <p>14. Fixed problem with title alignment adjustment on Web pages after firmware update.</p> <p>15. Correctly parse PCIe correctable error.</p> <p>16. Added support for the UEFI PXE boot device via Redfish.</p> <p>17. Allow SUM to trigger BMC to execute PCH reset action when SPS is downgraded.</p> <p>18. Corrected BMC memory leak.</p>
--	---