

# IPMI Firmware / BIOS Release Notes Form

*Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.*

<b>Product Name</b>	<b>H11DST-B-P (All)</b>
<b>Release Version</b>	<b>1.1c</b>
<b>Release Date</b>	<b>4/15/2019</b>
<b>Previous Version</b>	<b>1.1b</b>
<b>Update Category</b>	<b>Normal</b>
<b>Dependencies</b>	<b>N/A</b>
<b>Important Notes</b>	<b>BIOS Image: H11DST9.415 BIOS Update Package: H11DST9.415.ZIP</b>
<b>Enhancements</b>	<ol style="list-style-type: none"><li>1. Fixed inability of the website "AER/MCE ENABLE/DISABLE FOR XML FORMAT" to find the setting of item "Correctable Error Threshold".</li><li>2. Added vendor and status info to the driver health warning message.</li><li>3. Updated AGESA NaplesPI to 1.0.0.B based on AMI 5.013_NaplesCrb_0ACIJ021.</li><li>4. Changed secure boot keys to Supermicro secure boot keys.</li><li>5. Hid Driver Health page for SUM.</li><li>6. Updated valid range of IPMI setup item VLAN ID to 1-4094.</li><li>7. Enabled driver health message.</li><li>8. Updated ASPEED VBIOS to version 1.09.00.</li><li>9. Enhanced CPU and Memory compatibility.</li></ol>
<b>New features</b>	<b>N/A</b>
<b>Fixes</b>	<ol style="list-style-type: none"><li>1. Set the PCIe speed of ASPEED BMC to run as Gen1 to correct for issue of unexpected electrical idle signal causing AST2500 PCIe controller link failure.</li></ol>

	<ul style="list-style-type: none"><li>2. Fixed incorrect power supply characteristics of SMBIOS type 39.</li><li>3. Fixed inability of system to wake on PCIe LAN.</li><li>4. Fixed problem of system hanging when installing NVidia RTX 2080/5000/6000.</li><li>5. Fixed excessive delay of boot to enter login screen with Linux Redhat legacy OS.</li><li>6. Fixed compiler issue with SMCPKG_SUPPORT token for power button 4-second override.</li><li>7. Fixed problem of prefetchable memory size of root bridge allocating over 1M in close VGA decode phase.</li><li>8. Fixed display error of SIOM 1G Broadcom LAN MAC address.</li><li>9. Fixed problem of NVDIMM generating yellow bang in persistent memory of device manager.</li></ul>
--	--

***Release Notes from Previous Release(s)***

***1.1b (11/23/2018)***

1. Patched missing PSU information in BMC web if common header is empty.
2. Updated AGESA NaplesPI to 1.0.0.A based on AMI 5.013\_NaplesCrb\_0ACIJ020.
3. Upgraded memory speed from 2400 to 2666MHz when a 2R DIMM is installed in a channel.
4. Displayed the driver health support pages to support LSI (Broadcom 9440-8i) driver health status.

***1.1a (10/04/2018)***

1. Patched memory incompatibility and memory size reading issues.
2. Added CPU crash dump function.
3. Fixed failure of SUM test case 210.

***1.1 (08/21/2018)***

1. Updated AGESA NaplesPI to 1.0.0.9 based on AMI CRB\_019.
2. Updated Intel i350 PXE ROM to 1.5.84 and UEFI driver to 5.3.00.
3. Updated X540 PXE ROM to v2.3.64.
4. Fixed inability of Mellanox CX-4 to work in Linux when 2TB memory is installed.

***1.0c (05/02/2018)***

1. Updated AGESA NaplesPI to 1.0.0.7 based on AMI CRB\_017.
2. Added support for graphic Early Video mode.
3. Added support for hidden item "Memory Corrected Error Enabling" to disable OS logs' CECC error.
4. Added support for NVMe hotplug.
5. Fixed inability to execute the iSCSI OPROM of Intel x550 LAN card.
6. Updated AMI PSPDATA region and FV\_BB in recovery mode.
7. Fixed problem of UEFI LAN driver being executed when CSM is disabled and onboard LAN Option ROM Type is Legacy.
8. Fixed the location of SMCI signature in CMOS.
9. Fixed failure to preserve SMBIOS types 1 and 2 after flashing BIOS.
10. Fixed inability to preserve DMI data and some BIOS settings after SUM updates BIOS.

***1.0b (02/07/2018)***

1. Added AOC card support.
2. Added BPN-ADP-6NVMe3-1UB redriver.
3. Added Intel X550/X710 linkwidth workaround.
4. Revised SIOM information in SMBIOS Type 9.
5. Fixed inability to boot to PEX with external LAN card.
6. Updated AGESA NaplesPI to 1.0.0.5 based on AMI CRB\_014.
7. Fixed problem of system stopping in recovery mode when updating BIOS from 1.0a to 1.0b.