IPMI Firmware / BIOS Release Notes Form

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	H11DSi/H11DSi-NT
Release Version	1.46
Release Date	5/22/2019
Previous Version	1.38
Update Category	Recommended
Dependencies	BIOS v1.3
Important Notes	IPMI Image: SMT_H11AST2500_146.bin IPMI Update Package: SMT_H11AST2500_146.ZIP
Enhancements	 Adjusted the VDDCR threshold for all H11 projects. Improved SMBIOS data loss when AC is on. Improved the lack of SMBIOS data caused by the reset pin signal when AC is on. Patched for CVE-2019-6260 pantsdown. Updated the threshold of the AMD GPU (MI8/MI25). Changed the naming for Health Event Log & Maintenance Event Log in Web UI.
	 Moved NIC/GPU URLs from chassis/ into systems/. Changed the naming for Health Event Log & Maintenance Event Log in Redfish. Improved possible issues with setting up IPV6 and VLAN.
New features	 Added support for the riser feature with multi-chip. Enabled clearing all system event logs without generating any log and dumping all the system event logs.
Fixes	 Fixed inability of the power value of SPM to match the power value of IPMI and power meter. Fixed incorrect KEYPAD * and + key maps via IPMI iKVM console and KEYPAD on physical keyboard. Fixed issue with WebUI formatting. Fixed problem of degraded & unavailable SEL event appearing after Broadcom 3108 firmware is updated.
	5. Fixed mismatch of Redfish FullList Allowed Operation.

- 6. Fixed malfunction of KVM and remote control after using SSH in SMASH with AD account.
- 7. Fixed failure to save LDAP port to 389 after it was saved as SSL-enabled 636 in Web.
- 8. Fixed the issue of a fan error message appearing during AC ON/OFF test when the fan is not connected to the system.
- 9. Fixed problem of DCMS license activation showing inconsistent results between IPMI firmware 1.52 and 1.61.
- 10. Fixed DCMS check.
- 11. Fixed inability to detect MI25 GPU.
- 12. Fixed issue of "Save uncompleted" message appearing when changing time and saving it on IPMI Web.
- 13. Fixed multiple Web UI formatting issues.
- 14. Fixed the issue with CPU throttle.
- 15. Fixed missing deassert log after system recovers from CPU overheat.
- 16. Fixed inability to clean IPMI Hostname and issues of the session timing out after accessing system event log page and BMC continuously rebooting.
- 17. Fixed failure of IPMI SOL.
- 18. Added support for NVIDIA T4 GPU device.
- 19. Fixed malfunction of IPMI Web Date & Time Configuration.
- 20. Fixed failure of the system status to reference PSU state when AC is lost.
- 21. Fixed problem of BMC being damaged after running ARP stress test for over 24 hours.
- 22. Corrected pop-up message when deleting a group in Active Directory.
- 23. Fixed issue with BMC memory leak.
- 24. Corrected grammar error on the Alert page.
- 25. Fixed failure of NVMe Eject and insert Event log.

1.38 (05/30/2018)

- 1. Adjusted the SOCRUN threshold for all H11 projects.
- 2. Added new OEM commands for CPU power capping.
- 3. Fixed problem of BIOS screen reporting less memory after power cycle.
- 4. Fixed problem of IP Access Control Issue being reported from CRM #SM1806148647.
- 5. Fixed problem of EVENT SEVERITY in the email alert content being inconsistent with the info set on IPMI Configuration.
- 6. Fixed incorrect IPMI pop-up message when performing Factory Default on IPMI Web.
- 7. Fixed inability of BMC 1.37 to modify the event log on WebGUI.
- 8. Fixed inability to clean IPMI Hostname.
- 9. Fixed problem of sensor showing "RED" after every AC cycle chassis intrusion.
- 10. Fixed problem of NVMe temperature staying high on sensor reading page when NVMe temperature cools down.
- 11. Fixed failure of Redfish Automation Tool test.

1.34 (05/30/2018)

- 1. Adjusted the SOCRUN threshold for all H11 projects.
- 2. Added AMD-specific OEM command set 0x30 0x80 to read the current package power of CPU and set safe package power of CPU.
- 3. Fixed failure of Redfish Automation Tool.
- 4. Shortened the waiting time for the BMC to control the FAN speed when BMC starts.
- 5. Fixed problem of GPU1 appearing in BMC Web sensor list when GPU card is not installed.

1.27 (04/13/2018)

- Added support for Multi-Language Content on iKVM / HTML5 option menu and sub-menus.
- 2. Changed message format based on new specifications.
- 3. Fixed problem of CPU 2 Memory DIMM H1 (infrequently) dropping after off/on event.
- 4. Fixed failure of Redfish Automation Tool test.
- 5. Fixed problem of CPU fan duty cycle being unstable on standard or heavy IO in PUE2 mode.
- 6. Fixed problem of CPU fan duty cycle being inaccurate on PUE2 mode.
- 7. Fixed problem of Memory fan duty cycle being unstable on standard or heavy IO in PUE2 mode.
- 8. Fixed missing ECC/UECC DIMM Location in BIOS event log.
- 9. Fixed failure of SUM test.
- 10. Fixed failure of IPMI SUM test.
- 11. Fixed incorrect BMC fan speed control mode.