

IPMI Firmware

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

Product Name	X10SLH-F and X10SLM+-F
Release Version	3.81
Release Date	5/28/2019
Previous Version	3.72
Update Category	Recommended
Dependencies	None
Important Notes	None
Enhancements	<ol style="list-style-type: none">1. Improved Redfish webserver stability/performance.2. Corrected "Trouble Shooting" to "Troubleshooting".
New features	<ol style="list-style-type: none">1. Added support for AD/LDAP/RADIUS hostname.2. Added support for BBP2 PWS-1K01B-1R.3. Added syslog configuration support for IPv4 and IPv6 hostname.4. Added ability of SMCIPMITool to download Maintenance event log.5. Added advanced health event log.
Fixes	<ol style="list-style-type: none">1. Patched CVE-2019-6260 pantsdown security fix.2. IPMITool no longer hangs due to special characters &~`!@#\$%^*()_+={[] \; \"<,>./ in username and password.3. Improved webUI displays after AD configuration.4. Corrected Java SOL not launching a second time.5. Removed BMC memory leak.6. Detect PWS-721P power supply.7. Allow reading SMC power supply FRU.8. Allow setting user privilege to No Access via cmd.9. Changed 'event log' to 'health event log' and 'system event log' to 'maintenance event log'.10. Allow saving and restoring syslog configuration via maintenance-

	<p><i>>IPMI Configuration.</i></p> <ul style="list-style-type: none"><i>11. Prevent invalid IP format on IP Access Control page.</i><i>12. Clearing configuration no longer clears IP configuration.</i><i>13. Fixed issue with redfish/v1/Systems/1/Storage/HA-RAID/Volumes.</i><i>14. "Power Source" now shows up in IPMI WebGUI Server Health page.</i><i>15. Misc web page formatting.</i><i>16. IPMI no longer incorrectly parses PCIe correctable error to other description.</i><i>17. Added support for UEFI PXE boot device via Redfish.</i>
--	--