IPMI Firmware Release Notes

Supermicro disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade. All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Supermicro and the Supermicro logo are trademarks of Super Micro Computer, Inc. in the U.S. and/or other countries. Copyright © 2018 Super Micro Computer, Inc. All rights reserved.

| Product Name X11DPFR-S(N) Release Version 1.71.6 Release Date 8/30/2019 Previous Version 1.69 Update Category Recommended Dependencies None | |
|--|---|
| Previous Version 1.69 Update Category Recommended | |
| Update Category Recommended | |
| | |
| Dependencies None | |
| | |
| Important Notes None | |
| Enhancements N/A | |
| 1. Added support for third number (build ver | sion) of IPMI firmware version. |
| 2. Added BMC Account Security. | |
| 3. Added modification for event severity. | |
| New features 4. Enabled sending all event logs (Health & N | laintenance) to Syslog server. |
| 5. Added UefiPxe to Redfish System boot ord | |
| 6. Added support for DCPMM (AEP DIMM) si | |
| | |
| 1. Improve preserving BMC configuration aft | er updates. |
| 2. Added security fix for SSH-CLP. | |
| 3. CPU overheat deassertion no longer show | s system as critical in IPMI webUI. |
| 4. Updating Broadcom 3108 firmware no lon | ger shows error messages in SEL. |
| 5. Fixed multiple vulnerabilities with BMC Vi | rtual Media. |
| 6. Corrected maximum allowed password lea | gth shown for /redfish/v1/AccountService |
| MaxPasswordLength. | |
| 7. Corrected knymad * and I knyman via IBN | LiKVM and physical keyboard. |
| 8. Prevent IKVM/HTML5 being disabled in ce | |
| | reall instances. |
| 9. Improve web formatting for System tab. | Parkland Radio |
| 10. Factory default with RADIUS session no l | |
| 11. Improved Redfish for RADIUS: session die | connect after factory default; client returning localhost IP in |
| NAS-IP-Address; follow attribute 26 specifica | tion; prevent authentication error if delayed over 3 seconds. |
| 12. Improved stability of IPMI after updates. | |
| 13. Corrected formatting for minor version o | f Redfish - /Managers/1/FirmwareVersion. |