

# IoT SuperServer SYS-110P-FDWTR-NEBS-DC

Intel Xeon Socket P+ (LGA-4189) 3rd Gen, 600W -48 Vdc redundant PWS, NEBS Level 3 certified 1U edge platform



More details here

## Key Applications

Multi-Access Edge Computing (MEC), VRAN/ORAN for Telecom, Outdoor DU for 5G/RAN,


## Key Features

- NEBS Level 3 certified for Telecommunication;
- Socket P+ (LGA-4189) support 3rd Gen Intel® Xeon® Scalable processors;
- 8 DIMMs; Up to 2TB 3DS ECC DDR4-3200: RDIMM/LRDIMM;
- 2x 2.5" drive bays; 1 M.2 NVMe OR 1 M.2 SATA3;
- 6 heavy duty fans with optimal fan speed control; 1 Air Shroud(s);
- 600W Redundant Power Supplies Level (92%+);



<b>Form Factor</b>	1U Enclosure: 437 x 43 x 429mm (17.2" x 1.7" x 16.9") Package: 686 x 203 x 610mm (27" x 8" x 24")
<b>Processor</b>	Single Socket P+ (LGA-4189) 3rd Gen Intel® Xeon® Scalable processors Up to 32C/64T; Up to 48MB Cache
<b>System Memory</b>	Slot Count: 8 DIMM slots Max Memory (1DPC): Up to 2048GB 3200MT/s ECC DDR4 RDIMM/LRDIMM
<b>Drive Bays Configuration</b>	Default: Total 2 bays • 2 internal fixed 2.5" SATA drive bays M.2: 1 M.2 NVMe/SATA slot (M-key 2280/22110)
<b>Expansion Slots</b>	Default • 1 PCIe 4.0 x16 LP slot • 2 PCIe 4.0 x16 FHFL slots
<b>On-Board Devices</b>	SATA: SATA (6Gbps) ; RAID 0/1 support Network Connectivity: 2 RJ45 10GBASE-T with Intel® X550
<b>Input / Output</b>	USB: 2 USB 2.0 Type-A ports 2 Type-A ports Video: 1 VGA port

(Front View – System)



(Rear View – System)



System Cooling	Fans: Up to 6 heavy duty fans with optimal fan speed control Air Shroud: 1 Air Shroud
Power Supply	2x 600W Redundant (1 + 1) Typical 90%+ Level (96%) power supplies
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control Temperature: CPU thermal trip support, PEPI Monitoring for CPU and chassis environment
Dimensions and Weight	Weight: Gross Weight: 14.99 lbs (6.8 kg) Net Weight: 10.01 lbs (4.54 kg) Available Color: No Paint
Operating Environment	Operating Temperature: 0°C to 40°C (32°F to 104°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	<a href="#"><u>Super X12SPW-TF</u></a>
Chassis	<a href="#"><u>CSE-515B-R601W</u></a>