

# GPU SuperServer AS -4126GS-NMR-LCC

DP AMD 4U Liquid-Cooled System with AMD Instinct™ MI355X 8-GPU (onsite service is required for liquid-cooling)



## Key Applications

High Performance Computing, AI/Deep Learning Training, Industrial Automation, Healthcare, Conversational AI, Business Intelligence & Analytics, Drug Discovery, Climate and Weather Modeling, Finance & Economics,


## Key Features

- Dual processor(s) AMD EPYC™ 9005/9004 Series Processors up to 500W with Liquid Cooling;
- Supports up to 24 DIMMs slots, 6400 MT/s 6TB DDR5 in 1DPC (Please check System Memory Section for detail);
- Supports up to 8 PCIe 5.0 x16 LP + 2 PCIe 5.0 x16 FHHL slots;
- 2 RJ45 10GbE;
- Total of 8 front hot-swap 2.5" NVMe drive bays;
- 8x MI325x or MI355x onboard OAM GPU accelerator modules;
- Total of 4 Redundant (2+2) 6600W Titanium Level power supplies (Power supply full redundancy based on configuration and application load);




Form Factor	4U Rackmount Enclosure: 449 x 174 x 895.35mm (17.6" x 6.85" x 35.25") Package: 730 x 410 x 1280mm (28.7" x 16.14" x 50.39")
Processor	Dual processor(s) AMD EPYC™ 9005/9004 Series Processors Up to 384C/768T
GPU	Max GPU Count: Up to 8 onboard GPUs Supported GPU: AMD: Instinct™ MI355X Accelerators, Instinct™ MI325X Accelerators CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: AMD Infinity Fabric™ Link
System Memory	Slot Count: 24 DIMM slots Max Memory (1DPC): Up to 6TB 6400MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor) Max Memory (1DPC): Up to 6TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor)
Drive Bays Configuration	Default: Total 8 bays <ul style="list-style-type: none"> <li>• 8 front hot-swap 2.5" PCIe 5.0 x4 NVMe drive bays</li> </ul> M.2: 2 M.2 NVMe slots (M-key)
Expansion Slots	PCI-Express (PCIe) Configuration: Default <ul style="list-style-type: none"> <li>• 8 PCIe 5.0 x16 LP slots</li> <li>• 2 PCIe 5.0 x16 FHHL slots</li> </ul> M.2: 2 M.2 NVMe slots (M-key 22110(default))
On-Board Devices	System on Chip
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 Type-A ports(Rear) Video: 1 VGA port TPM: 1 TPM header

(Front View – System)



(Rear View – System)

**System Cooling**

Fans: Up to 5x 6cm heavy duty fans with optimal fan speed control  
 Air Shroud: 1 Air Shroud  
 Liquid Cooling: Direct to Chip (D2C) Cold Plate

**Power Supply**

4x 6600W Redundant (2 + 2) Titanium Level (96%) power supplies

**System BIOS**

BIOS Type: AMI 64MB SPI Flash EEPROM

**Management**

SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!

**PC Health Monitoring**

CPU: Monitors for CPU Cores, Chipset Voltages, Memory  
 FAN: Fans with tachometer monitoring  
 Status monitor for speed control  
 Pulse Width Modulated (PWM) fan connectors  
 Temperature: Monitoring for CPU and chassis environment  
 Thermal Control for fan connectors

**Dimensions and Weight**

Weight: Gross Weight: 140 lbs (63.5 kg)  
 Net Weight: 80 lbs (53 kg)  
 Available Color: Silver

**Operating Environment**

Operating Temperature: 10°C to 35°C (50°F to 95°F)  
 Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)  
 Operating Relative Humidity: 8% to 90% (non-condensing)  
 Non-operating Relative Humidity: 5% to 95% (non-condensing)

**Motherboard**

[\*\*Super H14DSG-OD\*\*](#)

**Chassis**

**CSE-GP403TS-R000NP2**