

# IoT SuperServer SYS-E300-13AD

Mini-1U Embedded System with 13th/12th Generation Intel® Core™, up to 16 cores



More details here

## Key Applications

Healthcare, Surveillance Security Server, AI Inference, Digital Signage / PoS,

## Key Features

- 13th/12th Generation Intel® Core™ i9/i7/i5/i3/Pentium/Celeron Processor (LGA-1700);
- Intel® Q670E;
- 2x DDR4-3200MHz SO-DIMM max 64GB;
- Support M.2 M/E-Key  
Support 1x PCIe 5.0 x16 Slot (Optional);
- AMT vPro Supported;
- Support up to 2x 2.5" drive bays (Optional);
- Quad Independent Display by 2x HDMI and 2x DP;




Form Factor	Fan-based Embedded Enclosure: 264.8 x 43 x 225.8mm (10.43" x 1.69" x 8.89") Package: 381 x 276 x 142mm (15" x 10.87" x 5.59")
Processor	Single LGA-1700 13th/12th Gen Intel® Core i9/Core i7/Core i5/Core i3/Pentium/Celeron processor Up to 16C/32T; Up to 30MB Cache
GPU	Max GPU Count: 1 single-width GPU Supported GPU: NVIDIA: RTX A400 NVIDIA PCIe: A1000, L4
System Memory	Slot Count: 2 DIMM slots Max Memory (2DPC): Up to 64GB 3200MT/s non-ECC DDR4 SO-DIMM
Drive Bays Configuration	Default: Total 1 bay • 1 internal fixed 2.5" SATA* drive bay (*SATA support may require additional storage controller and/or cables) M.2: 1 M.2 PCIe 4.0 x4 NVMe slot (M-key 2280)
Expansion Slots	PCI-Express (PCIe) Configuration: Default* • 1 PCIe 5.0 x16 (in x16) LP slot (*Requires additional parts, please see the optional parts list for details. For more details on PCIe slot configuration options, please refer to the system callout images above.) M.2: 1 M.2 PCIe 3.0 x1 slot (E-key 2230)
On-Board Devices	Chipset: Intel® Q670E Network Connectivity: 1 RJ45 1GbE with Intel® I210-AT 1 RJ45 2.5GbE with Intel® I225-LM
Input / Output	LAN: 1 RJ45 2.5 GbE LAN port (Intel® I225-LM) 1 RJ45 1 GbE LAN port (Intel® I210-AT) USB: 4 USB 3.2 Gen2 Type-A ports(Rear) Video: 1 HDMI 2.0b port(Rear) 1 HDMI 1.4 port(Rear) 2 DisplayPort ports(Rear) Audio: Line Out Mic in

(Front View – System)



(Rear View – System)

**System Cooling**

Fans: Up to 2x 4-PIN PWM 40x40x28mm Fan(s)  
Up to 1 CPU heatsink with  $\Phi$ 80x15mm Fan(s)

**Power Supply**

1x 180W power supply

**System BIOS**

BIOS Type: AMI 32MB SPI Flash  
BIOS Features: ACPI 6.0  
Plug and Play (PnP)  
RTC (Real Time Clock) Wakeup  
SPI dual/quad speed support

**Management**

SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!

**Dimensions and Weight**

Weight: Gross Weight: 7.5 lbs (3.4 kg)  
Net Weight: 3.7 lbs (1.6 kg)  
Available Color: Black

**Operating Environment**

Operating Temperature: 0°C to 40°C (32°F to 104°F) with 0.7 m/s airflow  
Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)  
Operating Relative Humidity: 8% to 90% (non-condensing)  
Non-operating Relative Humidity: 5% to 95% (non-condensing)

**Motherboard**

[Super X13SAV-LVDS](#)

**Chassis**

**CSE-E300**